

## Toward a computational tool to simulate for the flame propagation in thermites powders

Emilian Tichtchenko, Pillemont Léa, Benoît Bédat, Olivier Simonin, Ludovic Glavier, Alain Esteve, Carole Rossi

## ► To cite this version:

Emilian Tichtchenko, Pillemont Léa, Benoît Bédat, Olivier Simonin, Ludovic Glavier, et al.. Toward a computational tool to simulate for the flame propagation in thermites powders. Europyro 2023, Af3P (Association Française de Pyrotechnie); GTPS (Groupe de Travail de Pyrotechnie), Sep 2023, Saint Malo, France. hal-03922512

## HAL Id: hal-03922512 https://laas.hal.science/hal-03922512

Submitted on 17 Oct 2023  $\,$ 

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## Toward a computational tool to simulate for the flame propagation in thermites powders

Emilian Tichtchenko<sup>a,c</sup>, Pillemont Léa<sup>a</sup>, Benoit Bedat<sup>b</sup>, Olivier Simonin<sup>b</sup>, Ludovic Glavier<sup>c</sup>, Alain Esteve<sup>a</sup>, Carole Rossi<sup>a</sup>

> <sup>a</sup>LAAS, University of Toulouse, CNRS-UPR 8001, France <sup>b</sup>IMFT, University of Toulouse, CNRS-UMR 5502, France <sup>c</sup> ArianeGroup SAS, 66 Route de Verneuil, 78130 Les Mureaux, France

Mixtures of metal/metal-oxide, commonly known as thermite, can burn in a self-sustained reaction with an ultra-high energy density [1-2]. The high combustion temperature, safety, and tunability of thermites make it possible to produce totally novel pyrotechnical devices for inspace maneuvers (stage separation, pulse power generation for extended space missions, ...) [3-4]. However, the effective transfer of thermites from research laboratories to industrial products faces a core challenge, which is the lack of realistic deflagration models to guide the system design. Thus, the customization of a thermite mixture is still guided more or less by empirical considerations mostly from observations in flame tube experiments or using the empirical "Edisonian" approach, based on trial-and-error. Both approaches are totally inadequate to explore the large number of possible metals and oxides, in which not only the chemistry but also the microscopic (particle scale) and mesoscopic properties (systems of particles) influence the macroscopic combustion. This paper presents a one-dimensional (1D) model that simulates Al reaction propagation when in contact with a strong oxidizer in a cylindrical tube. CuO was chosen as it is the widest used metallic oxidizer that decomposes below the reaction temperature. In addition to condensed phase theory [5], representations of the gas phase combustion at the different scale is implemented using a computational fluid dynamics scheme enabling to model multiphase physics and combined physico-chemical mechanisms [6] taking place during the thermite reaction which are all extremely important factors to account for.

The model is designed as a combustion tube as used for flame speed measurements, i.e. with rigid walls filled with homogenous mixture of Al and CuO particles. The Al particle richness, the powder density, the particles diameters, and stoichiometric ratio and heat loss through the wall define the main parameters of the system. The 1D heat flow equation is coupled with mass and momentum equations and both diffusion and advection are considered. The calculated values of flame velocity show a reasonable compatibilit ywith the experimental data.

Reference:

(1) Pantoya, M. L.; Granier, J. J. Combustion Behavior of Highly Energetic Thermites: Nano versus Micron Composites. *Propellants, Explosives, Pyrotechnics* **2005**, *30* (1), 53–62.

(1) Zapata, J.; Nicollet, A.; Julien, B.; Lahiner, G.; Esteve, A.; Rossi, C. Self-Propagating Combustion of Sputter-Deposited Al/CuO Nanolaminates. *Combustion and Flame* **2019**, *205*, 389–396.

(4) Finazzi, A.; Maggi, F.; Paravan, C.; Galfetti, L.; Dossi, S.; Murgia, A.; Lips, T.; Smet, G. Thermite-for-Demise (T4D): Concept Definition for Exothermic Reaction-Aided Spacecraft Demise during Re-entry, *EUCASS* 22, 9<sup>TH</sup> European Conference for Aeronautics and Space Science, Lille, France, 27 June-1 July **2022** 

- (5) Larangot, B.; Rossi, C.; Camps, T.; Berthold, A.; Pham, P.; Briand, D.; Puig-Vidal, M.; Miribel, P.; Esteve,
- D.; Rooij, N. D.; Montanes, E.; Macias, G.; Samitier, J. Solid Propellant Micro Rockets Towards a New Type of Power MEMS, *NanoTech* 2002 "At the Edge of Revolution" Houston, Texas, 9-12 September 2002

<sup>(3)</sup> Rossi, C.; Larangot, B.; Pham, P. Q.; Briand, D.; de Rooij, N. F.; Puig-Vidal, M.; Samitier, J. Solid propellant microthrusters on silicon: Design, modeling, fabrication, and testing, *J Microelectromech S*, **2006**, *15* (6), 1805-1815

(5) Lahiner, G.; Nicollet, A.; Zapata, J.; Marín, L.; Richard, N.; Rouhani, M. D.; Rossi, C.; Estève, A. A Diffusion–Reaction Scheme for Modeling Ignition and Self-Propagating Reactions in Al/CuO Multilayered Thin Films. *Journal of Applied Physics* **2017**, *122* (15), 155105.

(6) Tichtchenko, E.; Folliet, V.; Simonin, O.; Bedat, B.; Glavier, L.; Esteve, A.; Rossi, C. Combustion model for thermite materials integrating explicit and coupled treatment of condensed and gas phase kinetics, *Proc. Combust. Inst.*, **2022**, *1-9*.