

# Linear programming based lower bounds on average dwell-time via multiple Lyapunov functions

Sigurdur Hafstein, Aneel Tanwani

# ▶ To cite this version:

Sigurdur Hafstein, Aneel Tanwani. Linear programming based lower bounds on average dwelltime via multiple Lyapunov functions. European Journal of Control, 2023, 74, pp.100838. 10.1016/j.ejcon.2023.100838 . hal-04161620

# HAL Id: hal-04161620 https://laas.hal.science/hal-04161620v1

Submitted on 13 Jul 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Linear Programming based Lower Bounds on Average Dwell-Time via Multiple Lyapunov Functions

Sigurdur Hafstein<sup>a</sup>, Aneel Tanwani<sup>b</sup>

<sup>a</sup>University of Iceland, Faculty of Physical Sciences, Dunhagi 5, Reykjavik, 107, Iceland <sup>b</sup>CNRS – LAAS, University of Toulouse, Toulouse, France

## Abstract

With the objective of developing computational methods for stability analysis of switched systems, we consider the problem of finding the minimal lower bounds on average dwell-time that guarantee global asymptotic stability of the origin. Analytical results in the literature quantifying such lower bounds assume existence of multiple Lyapunov functions that satisfy some inequalities. For our purposes, we formulate an optimization problem that searches for the optimal value of the parameters in those inequalities and includes the computation of the associated Lyapunov functions. In its generality, the problem is nonconvex and difficult to solve numerically, so we fix some parameters which results in a linear program (LP). For linear vector fields described by Hurwitz matrices, we prove that such programs are feasible and the resulting solution provides a lower bound on the average dwell-time for exponential stability. Through some experiments, we compare our results with the bounds obtained from other methods in the literature and we report some improvements in the results obtained using our method.

*Keywords:* Switched systems, continuous piecewise-affine Lyapunov functions, average dwell-time, linear programs

### 1. Introduction

Switched systems comprise a family of dynamical subsystems orchestrated by
 a switching signal that activates one of these subsystems at a given time. This
 abstract framework has been useful in modeling a class of hybrid systems with

*Email addresses:* shafstein@hi.is (Sigurdur Hafstein), aneel.tanwani@cnrs.fr (Aneel Tanwani)

continuous and discrete dynamics. Another common source of switched systems
is uncertainty quantification in continuous-time systems and the associated differential inclusions. Stability analysis of switched systems, therefore, has gathered a
lot of attention in the literature. The references [16, 25] provide a comprehensive
overview of the different approaches on this topic.

When analyzing stability under arbitrary switching, existence of a common 10 Lyapunov function is a necessary and sufficient condition for the asymptotic sta-11 bility of an equilibrium of the switched system [6]. Thus, over the years, a lot 12 of attention in the literature has been given to computing a common Lyapunov 13 function for the switched system under different hypotheses. For some results in 14 this direction, the reader may refer to [1] for discrete-time systems, and [22] for 15 continuous-time systems. Particularly relevant to this paper is the technique based 16 on the construction of continuous and piecewise affine (CPA) Lyapunov functions, 17 which is reviewed in [11]. The papers [3, 13] present the adaptation of computing 18 CPA Lyapunov functions in case of arbitrarily switching systems. However, such 19 methods have not yet been used in the context of constrained, or dwell-time based, 20 switched systems. 21

For certain applications, existence of common Lyapunov function is a strin-22 gent requirement, and may not hold for the given system data. For that reason, 23 when the individual subsystems are asymptotically stable and one can not com-24 pute a common Lyapunov function, it is natural to ask how we can guarantee 25 26 stability for a certain class of switching signals (which is smaller than the set of switching signals with arbitrary switching). The works [21] and [14] studied the 27 stability of switched systems by putting a bound on how fast the switches can 28 occur. Depending on the system data, lower bounds were derived on the (aver-20 age) dwell-time which ensures global asymptotic stability if the length of interval 30 between two consecutive switches (on average) is greater than the derived lower 31 bound. A tutorial like exposition of these concepts also appears in [16, Chap-32 ter 3]. Several works have followed up to extend this idea in several directions. 33 Some generalizations have been addressed in the recent papers [18, 23] with non-34 linearities in the system data. 35

Computational methods with multiple Lyapunov functions for getting best possible lower bounds on the dwell-time have not received much attention in the literature. The references [4, 7, 17, 20] provide some algorithms for calculating lower bounds on the dwell-time in the linear case. Among these, the papers [17, 20] build on dwell-time bounds obtained from multiple Lyapunov functions, which is also the case for this article. The authors of [20] developed optimizationbased methods for the automatic verification of dwell-time properties. On the

other hand, [17] proposes some relaxations in the form of sequential convex pro-43 grams to compute lower bounds on the average dwell-time. With similar motiva-44 tion, this article studies computational methods for computing best possible lower 45 bounds on the (average) dwell-time using linear programming (LP) methods. In 46 fact, our approach uses techniques based on the construction of CPA Lyapunov 47 functions, under the constraints that are normally imposed for dwell-time based 48 stability conditions. For a given family of dynamical subsystems with asymptoti-49 cally stable origin, the question of interest is to find the *smallest* lower bound on 50 the dwell-time, which ensures asymptotic stability of the switched system under 51 the so-called compatibility constraints. Such questions can be formulated as an 52 optimization problem and in its full generality, it is a nonconvex problem, even 53 when dealing with linear subsystems and quadratic Lyapunov functions for indi-54 vidual subsystems. 55

In this paper, we provide a new technique for solving the optimization prob-56 lem that corresponds to the computation of a minimum average dwell-time that 57 ensures stability. The intermediate step in getting this bound is to first compute 58 the Lyapunov functions for individual subsystems satisfying certain inequalities. 59 In our work, we search for these Lyapunov functions from the family of continu-60 ous piecewise affine functions, in contrast to the quadratic ones. This is done by 61 discretizing the state space into simplices and solving for the values of the Lya-62 punov functions at the vertices of the simplices, using some inequality constraints. 63 The resulting optimization problem actually turns out to be a linear program. The 64 solution to this linear program provides us with a Lyapunov function for each 65 subsystem and also a dwell-time bound. 66

The remainder of the paper is organized as follows: we recall some basic results on (average) dwell-time stability in Section 2 and describe the problem being studied in this paper. Section 3 provides the LP formulation of the proposed problem along with some results about the feasibility of these programs. We provide some simulations and comparisons with other methods in Section 4, followed by concluding remarks in Section 5.

### 73 2. Problem Setup

<sup>74</sup> We consider time-dependent switched dynamical systems described as

$$\dot{\mathbf{x}} = \mathbf{f}_{\sigma}(\mathbf{x}) \tag{1}$$

where, for some given index set  $\mathcal{P} \subset \mathbb{N}$ , the function  $\sigma : [0, \infty) \to \mathcal{P}$  is piecewise

<sup>76</sup> constant and right-continuous, called the *switching signal*. The discontinuities of

<sup>77</sup>  $\sigma$ , called the *switching times*, are assumed to be locally finite. The vector fields <sup>78</sup>  $\mathbf{f}_i : \mathbb{R}^n \to \mathbb{R}^n$ , for each  $i \in \mathcal{P}$ , are assumed to be locally Lipschitz and with <sup>79</sup>  $\mathbf{f}_i(\mathbf{0}) = \mathbf{0}$ . We say that a switching signal  $\sigma$  has an average dwell-time  $\tau_a > 0$ , if <sup>80</sup> there exists  $N_0 > 0$ , such that

$$N_{\sigma}(t,s) \le N_0 + \frac{t-s}{\tau_a},$$

where  $N_{\sigma}(t,s)$  denotes the number of switches over the interval (s,t). The set of all switching signals with average dwell-time  $\tau_a$  is denoted by  $\Sigma_{\tau_a}$ .

For the stability of the origin for such systems, let us recall the following result, which follows from [14], [16, Chapter 3], and [18, Theorem 1]:

**Theorem 1.** Suppose that there exist  $C^1$  Lyapunov functions  $V_p : \mathbb{R}^n \to \mathbb{R}_{\geq 0}$ , i  $\in \mathcal{P}$ , satisfying the following:

<sup>87</sup> **(L1)** There exist  $\underline{\alpha}, \overline{\alpha} \in \mathcal{K}_{\infty}$  such that

$$\underline{\alpha}(\|\mathbf{x}\|) \le V_i(\mathbf{x}) \le \overline{\alpha}(\|\mathbf{x}\|), \quad \forall \mathbf{x} \in \mathbb{R}^n, i \in \mathcal{P}.$$
(2)

<sup>88</sup> (L2) There exists a Lipschitz function  $\rho \in \mathcal{K}$ , such that, for every  $i \in \mathcal{P}$ ,

$$\nabla V_i(\mathbf{x}) \cdot \mathbf{f}_i(\mathbf{x}) \le -\rho(V_i(\mathbf{x})) \quad \forall \mathbf{x} \in \mathbb{R}^n,$$
(3)

<sup>89</sup> **(L3)** There exists  $\chi \in \mathcal{K}_{\infty}$  such that, for every  $i, j \in \mathcal{P}$ ,

$$V_j(\mathbf{x}) \le \chi(V_i(\mathbf{x})) \quad \forall \mathbf{x} \in \mathbb{R}^n, i \ne j.$$
 (4)

- <sup>90</sup> Then the origin is globally asymptotically stable for the switched system (1), uni-
- <sup>91</sup> formly over the set  $\Sigma_{\tau_a}$ , for  $\tau_a$  satisfying

$$\tau_a > \sup_{s>0} \int_s^{\chi(s)} \frac{1}{\rho(r)} dr.$$
(5)

The lower bound on the average dwell-time given in (5), with nonlinear functions, has also appeared in the context of impulsive systems in [24], [5]. In what follows, we will restrict ourselves to linear subsystems where the functions  $\alpha$  and  $\rho$  can be taken as linear. Writing (5) for such cases allows us to better understand the degrees of freedom at our disposal for minimizing the lower bounds on  $\tau_a$ .

#### 97 2.1. Corollaries and special cases

Let us present two corollaries to this result depending on the class of functions of chosen for  $V_i$  and the vector fields  $\mathbf{f}_i$ ,  $i \in \mathcal{P}$ .

**Corollary 1.** Assume that for each  $i \in \mathcal{P}$ , there exist symmetric, positive definite matrices  $P_i \succ 0$ , such that

$$A_i^{\top} P_i + P_i A_i + \alpha P_i \preceq 0, \quad \text{for every } i \in \mathcal{P},$$
(6a)

$$P_j \preceq \mu P_i, \quad \text{for every } j \neq i$$
 (6b)

for some  $\alpha > 0$  and  $\mu \ge 1$ . Then the switched system (1) with  $\mathbf{f}_i(\mathbf{x}) = A_i \mathbf{x}$ ,  $i \in \mathcal{P}$ , has a globally exponentially stable equilibrium at the origin, uniformly over the set  $\Sigma_{\tau_a}$ , where  $\tau_a$  satisfies

$$\tau_a > \frac{\ln(\mu)}{\alpha}.\tag{7}$$

Thus, for linear dynamics and quadratic Lyapunov functions, we can get a lower bound on the average dwell-time by solving matrix inequalities (6). If we take,  $\alpha > 0$ ,  $\mu \ge 1$ , and  $P_i \succ 0$  as the unknowns in (6), then these inequalities are not linear with respect to the unknowns, and it is difficult to compute a solution. The article [17] addresses the problem of minimizing  $\frac{\ln(\mu)}{\alpha}$  subject to inequalities (6) by proposing convex relaxations.

For the algorithms proposed in this paper, we first need a corollary to Theorem 1 with continuous Lyapunov functions, and norm-like bounds on the growth and Dini-derivative of such functions. For a continuous function  $V : \mathbb{R}^n \to \mathbb{R}$ , we define the Dini-derivative along the solutions of the system  $\dot{\mathbf{x}} = \mathbf{f}_i(\mathbf{x})$  as

$$D^+V(\mathbf{x}, \mathbf{f}_i(\mathbf{x})) := \limsup_{h \to 0+} \frac{V(\boldsymbol{\phi}_i(h, \mathbf{x})) - V(\mathbf{x})}{h}$$

where  $t \mapsto \phi_i(t, \mathbf{x})$  is an absolutely continuous function that satisfies  $\phi_i(0, \mathbf{x}) = \mathbf{x}$  and  $\dot{\phi}_i(t, \mathbf{x}) = \mathbf{f}_i(\phi_i(t, \mathbf{x}))$  almost surely for  $t \ge 0$ . We use this notion to state the following corollary to Theorem 1, obtained by taking  $\underline{\alpha}$ ,  $\overline{\alpha}$ ,  $\rho$  to be homogenue nous functions, and  $\chi$  being linear.

**Corollary 2.** Assume that for each  $i \in \mathcal{P}$ , there exist continuous functions  $V_i : \mathbb{R}^n \to \mathbb{R}$ , such that

$$\underline{a} \|\mathbf{x}\|^{d} \le V_{i}(\mathbf{x}) \le \overline{a} \|\mathbf{x}\|^{d}, \quad \text{for every } i \in \mathcal{P},$$
(8a)

$$D^+V_i(\mathbf{x}, \mathbf{f}_i(\mathbf{x})) \le -\alpha \|\mathbf{x}\|^d, \quad \text{for every } i \in \mathcal{P},$$
(8b)

$$V_i(\mathbf{x}) \le \mu V_j(\mathbf{x}), \quad \text{for every } j \ne i.$$
 (8c)

for some d > 0,  $\overline{a} \ge \underline{a} > 0$ ,  $\alpha > 0$  and  $\mu \ge 1$ ; Then the switched system  $\dot{\mathbf{x}} = \mathbf{f}_{\sigma}(\mathbf{x})$  has a globally exponentially stable equilibrium at the origin, uniformly over the set  $\Sigma_{\tau_a}$ , with  $\tau_a$  satisfying,

$$\tau_a > \frac{\overline{a}\ln(\mu)}{\alpha}.\tag{9}$$

In contrast to Theorem 1, the proof of Corollary 2 using Dini derivative requires some care but essentially follows similar concepts. In this paper, we will build on the statement of Corollary 2 and, in particular, address the following problem:

Problem statement. With d = 1 and for fixed values of  $\underline{a} > 0$ ,  $\overline{a} > 0$ , and  $\mu \ge 1$ , find piecewise linear functions  $V_i$ , for each  $i \in \mathcal{P}$ , that satisfy (8) while maximizing  $\alpha$ .

The reason for fixing the constants  $\underline{a} > 0$ ,  $\overline{a} > 0$ , and  $\mu \ge 1$  is that the foregoing problem then transforms into a linear program. We will provide the formulation of this linear program and discuss its feasibility in the next section. For the sake of clarity in this conference paper, we present our ideas for the linear vector fields but similar concepts can be extended to nonlinear systems.

### <sup>131</sup> 2.2. *Quadratic functions and matrix inequalities*

Before discussing the LP problem and CPA Lyapunov functions, let us first look at the inequalities (8) for the case d = 2 more carefully. In this case, we let  $V_i(\mathbf{x}) = \mathbf{x}^\top P_i \mathbf{x}$ , with symmetric and positive definite  $P_i \in \mathbb{R}^{n \times n}$ . In particular, (8) takes the following form, where I is the identity matrix:

$$\begin{cases} \underline{a}I \leq P_i \leq \overline{a}I, & i \in \mathcal{P}, \\ A_i^\top P_i + P_i A_i \leq -\alpha I, & i \in \mathcal{P}, \\ P_i \leq \mu P_j, & i, j \in \mathcal{P}. \end{cases}$$
(10)

In (10), if we fix  $\underline{a}, \overline{a} > 0$  and  $\mu \ge 1$ , then the inequalities result in LMIs with unknowns  $P_i$ ,  $i \in \mathcal{P}$ , which can be solved to maximize  $\alpha$ . Practically one can select  $\underline{a}$  small, e.g.  $\underline{a} = 10^{-5}$  as we do in our examples, and then a large enough  $\overline{a} > 0$  will ensure that  $\tau_a = \overline{a} \ln(\mu) / \alpha$  can be made minimal for the given  $\mu \ge 1$  by maximizing  $\alpha$ . Indeed, assume the conditions (10) are fulfilled for some positive constants  $\underline{a} = \underline{a}^*, \overline{a} = \overline{a}^*, \alpha = \alpha^*$  and  $V_i(\mathbf{x}) = \mathbf{x}^\top P_i^* \mathbf{x}, P_i^* \in \mathbb{R}^{n \times n}$  symmetric,  $i \in \mathcal{P}$ . Then we have the lower bound  $\tau_a^* = \overline{a}^* \ln(\mu) / \alpha^*$  on the average dwelltime. Now fix new constants  $\underline{a}, \overline{a} > 0$  such that  $\overline{a}/\underline{a} \ge \overline{a}^*/\underline{a}^*$  and set  $\alpha =$   $(\overline{a}/\overline{a}^*)\alpha^*$  and  $P_i = (\overline{a}/\overline{a}^*)P_i^*$ . Then, for  $V_i(\mathbf{x}) := \mathbf{x}^\top P_i \mathbf{x} = (\overline{a}/\overline{a}^*)\mathbf{x}^\top P_i^* \mathbf{x}$ , we have  $V_i(\mathbf{x}) \leq \mu V_j(\mathbf{x})$ , and

$$\underline{a} \|\mathbf{x}\|^2 \leq \underline{a}^* \frac{\overline{a}}{\overline{a}^*} \|\mathbf{x}\|^2 \leq V_i(\mathbf{x}) = (\overline{a}/\overline{a}^*) \mathbf{x}^\top P_i^* \mathbf{x} \leq \overline{a} \|\mathbf{x}\|^2$$

for  $i, j \in \mathcal{P}$ . That is, the constraints (10) are fulfilled with these values of  $\underline{a}, \overline{a}, \alpha, P_i$  and further, for the lower bound on the average dwell-time we have

$$\tau_a = \frac{\overline{a}\ln(\mu)}{\alpha} = \frac{\overline{a}\ln(\mu)}{\frac{\overline{a}\alpha^*}{\overline{a^*}}} = \frac{\overline{a^*}\ln(\mu)}{\alpha^*} = \tau_a^*.$$

In other words, for a fixed  $\mu \ge 1$ , if there is a solution to (10) for some choice of  $\underline{a}^*, \overline{a}^*, \alpha^*$  which yields the bound  $\tau_a^*$  for the average dwell-time, then by choosing  $\overline{a}/\underline{a}$  large enough, one can always find another solution to (10) which gives at least as good a bound on average dwell-time as  $\tau^*$ . Thus, given  $\mu \ge 1$ , maximizing  $\alpha > 0$  under the constraints (10) for a fixed  $\underline{a}, \overline{a} > 0$  delivers as good lower bounds on the average dwell-time  $\tau_a$  as minimizing  $\tau_a = \overline{a} \ln(\mu)/\alpha$ , where both  $\overline{a}$  and  $\alpha$ are variables, given that  $\overline{a}/\underline{a}$  is large enough.

Note that in the setting of the LMI problem (10) we are searching for quadratic Lyapunov functions for the individual subsystems  $\dot{\mathbf{x}} = A_i \mathbf{x}$ ,  $i \in \mathcal{P}$ , which can be conservative. In the next section we consider a similar approach for modeling the conditions (8) using piecewise linear Lyapunov functions and an LP formulation to compute them. Due to the foregoing observation, when solving (8) using an LP formulation, we will fix  $\underline{a}$  and  $\overline{a}$  with  $\underline{a}/\overline{a}$  large enough and maximize  $\alpha$ .

# 3. Continuous Piecewise Affine Lyapunov Functions and Linear Program ming Formulation

Our LP approach to compute piecewise linear Lyapunov functions fulfilling the conditions (8) is based on the so-called CPA method to compute Lyapunov functions, see e.g. [19, 3, 10, 13]. Its description is somewhat more involved than the LMI approach, because it is based on partitioning a neighborhood of the origin into simplices and the underlying idea behind constructing this collection of simplices, called *triangulation*, is described in the next subsection.

## 157 3.1. The Triangulation $\mathcal{T}_{K}^{\mathbf{F}}$

Roughly speaking, a triangulation is the subdivision of a subset of  $\mathbb{R}^n$  into simplices. A suitable concrete triangulation for our aim of parameterizing Lyapunov

functions for the individual subsystems is the triangular-fan of the triangulation in [8], where its efficient implementation is also discussed. In its definition, we use the functions  $\mathbf{R}^{\mathcal{J}} : \mathbb{R}^n \to \mathbb{R}^n$ , defined for every  $\mathcal{J} \subset \{1, 2, ..., n\}$  by

$$\mathbf{R}^{\mathcal{J}}(\mathbf{x}) := \sum_{i=1}^{n} (-1)^{\mathbb{1}_{\mathcal{J}}(i)} x_i \mathbf{e}_i,$$

where  $\mathbf{e}_i$  is the standard *i*th unit vector in  $\mathbb{R}^n$ , and  $\mathbb{1}_{\mathcal{J}}(i) = 1$  if  $i \in \mathcal{J}$  and 0 otherwise. Thus,  $\mathbf{R}^{\mathcal{J}}(\mathbf{x})$  is the vector  $\mathbf{x}$ , except for a minus has been put in front of the coordinate  $x_i$  whenever  $i \in \mathcal{J}$ .

We first define the triangulation  $\mathcal{T}^{\text{std}}$  and use it to construct the intermediate triangulation  $\mathcal{T}_K$ , which in turn is used to define our desired triangulation  $\mathcal{T}_K^{\mathbf{F}}$ .

The standard triangulation  $\mathcal{T}^{\text{std}}$  consists of the simplices

$$\mathfrak{S}_{\mathbf{z}\mathcal{J}\rho} := \operatorname{co}\left\{\mathbf{x}_{0}^{\mathbf{z}\mathcal{J}\rho}, \mathbf{x}_{1}^{\mathbf{z}\mathcal{J}\rho}, \dots, \mathbf{x}_{n}^{\mathbf{z}\mathcal{J}\rho}\right\}.$$

<sup>163</sup> where co denotes the convex hull, and

$$\mathbf{x}_{j}^{\mathbf{z}\mathcal{J}\rho} := \mathbf{R}^{\mathcal{J}}\left(\mathbf{z} + \sum_{i=1}^{j} \mathbf{e}_{\rho(i)}\right),\tag{11}$$

for all  $\mathbf{z} \in \mathbb{N}_0^n = \{0, 1, \ldots\}^n$ , all  $\mathcal{J} \subset \{1, 2, \ldots, n\}$ , all  $\rho \in S_n$ , and  $j = 0, 1, \ldots, n$ . Here,  $S_n$  denotes the set of all permutations of  $\{1, 2, \ldots, n\}$ .

Now fix a  $K \in \mathbb{N}_+ = \{1, 2, ...\}$  and define the hypercube  $\mathcal{H}_K := [-K, K]^n$ . 166 Consider the simplices  $\mathfrak{S}_{\mathbf{z}\mathcal{J}\rho} \subset \mathcal{H}_K$  in  $\mathcal{T}^{std}$ , that intersect the boundary of  $\mathcal{H}_K$ . 167 We are only interested in those intersections that are (n-1)-simplices, i.e. we 168 take every simplex with vertices  $\mathbf{x}_j := \mathbf{R}^{\mathcal{J}} \left( \mathbf{z} + \sum_{i=1}^j \mathbf{e}_{\rho(i)} \right), j \in \{0, 1, \dots, n\},$ 169 where exactly one vertex  $\mathbf{x}_{i^*}$  satisfies  $\|\mathbf{x}_{i^*}\|_{\infty} < K$  and the other n of the n+1170 vertices satisfy  $\|\mathbf{x}_j\|_{\infty} = K$ , i.e. for  $j \in \{0, 1, \dots, n\} \setminus \{j^*\}$ . Then we replace 171 the vertex  $\mathbf{x}_{j^*}$  by 0; it is not difficult to see that  $j^*$  is necessarily equal to 0. The 172 collection of such vertices triangulates  $\mathcal{H}_K$  and this new triangulation of  $\mathcal{H}_K$  is 173 our desired triangulation  $\mathcal{T}_K$ . 174

It has been shown [2] that it is often advantageous in the CPA method to map the vertices of the triangulation by the mapping  $\mathbf{F} \colon \mathbb{R}^n \to \mathbb{R}^n$ ,  $\mathbf{F}(\mathbf{0}) = \mathbf{0}$  and

$$\mathbf{F}(\mathbf{x}) := \frac{\|\mathbf{x}\|}{\|\mathbf{x}\|_{\infty}} \mathbf{x}, \quad \text{if } \mathbf{x} \neq \mathbf{0}.$$
(12)



(b) The triangulation  $\mathcal{T}_5^{\mathbf{F}}$  in three dimension; note that the origin is a vertex of all the tetrahedra in  $\mathcal{T}_5^{\mathbf{F}}$ .

Figure 1: Our proposed triangulation in  $\mathbb{R}^2$  and  $\mathbb{R}^3$ .

Note that **F** maps the hypercubes  $\{\mathbf{x} \in \mathbb{R}^n : \|\mathbf{x}\|_{\infty} = r\}$  to the spheres  $\{\mathbf{x} \in \mathbb{R}^n : \|\mathbf{x}\| = r\}$ .

Finally, we define the triangulation  $\mathcal{T}_{K}^{\mathbf{F}}$  that will be used in the LP problem to parameterize CPA Lyapunov functions. Let  $\mathcal{T}_{K}^{\mathbf{F}}$  be the triangulation consisting of the simplices

$$\mathfrak{S}_{\nu} := \operatorname{co}\{\mathbf{0}, \mathbf{F}(\mathbf{x}_{1}^{\nu}), \mathbf{F}(\mathbf{x}_{2}^{\nu}), \dots, \mathbf{F}(\mathbf{x}_{n}^{\nu})\},\$$

where

$$\operatorname{co}\left\{\mathbf{0},\mathbf{x}_{1}^{\mathbf{z}\mathcal{J}\rho},\mathbf{x}_{2}^{\mathbf{z}\mathcal{J}\rho},\ldots,\mathbf{x}_{n}^{\mathbf{z}\mathcal{J}\rho}
ight\}\in\mathcal{T}_{K}.$$

The subset of  $\mathbb{R}^n$  subdivided into simplices by the triangulation  $\mathcal{T}_K^{\mathbf{F}}$  is denoted by

$$\mathcal{D}_{\mathcal{T}^{\mathbf{F}}_{K}} := igcup_{\mathfrak{S}_{
u} \in \mathcal{T}^{\mathbf{F}}_{K}} \mathfrak{S}_{
u}.$$

Figure 1 depicts two exemplary triangulations of the type  $\mathcal{T}_{K}^{\mathbf{F}}$  for two and three dimension with K = 5. The implementation of the triangulation is discussed in [12, 9].

182 3.2. LP Problem

We are now ready to state our LP problem to parameterize piecewise linear Lyapunov functions for the switched system fulfilling the conditions in (8). For formulating this LP, and showing that its feasibility provides us the lower bound on average dwell-time, we focus our attention on the switched linear systems:

$$\dot{\mathbf{x}} = A_{\sigma} \mathbf{x} \tag{13}$$

with  $\sigma: [0, \infty) \to \mathcal{P}$  being the switching signal, and  $A_i \in \mathbb{R}^{n \times n}$ , for each  $i \in \mathcal{P}$ . We use three constants  $\underline{a}, \overline{a} > 0$  and  $\mu \ge 1$  in the LP problem. We want the ratio  $\overline{a}/\underline{a}$  to be large, as discussed in the last section, and then we want to try out different  $\mu \ge 1$  to obtain as good a lower bound on the average dwell-time as possible.

The variables of the LP problem are  $\alpha \in \mathbb{R}$  and  $V_{\mathbf{x},i} \in \mathbb{R}$  for every vertex  $\mathbf{x}$  of a simplex in  $\mathcal{T}_{K}^{\mathbf{F}}$  and every  $i \in \mathcal{P}$ .

- <sup>194</sup> The objective of the LP problem is to maximize  $\alpha$ .
- <sup>195</sup> The constraints of the LP problem are:
- (C1) The first set of constraints is that, for every  $i \in \mathcal{P}$ , we set  $V_{\mathbf{0},i} = 0$ , and for every vertex  $\mathbf{x}$  of a simplex in  $\mathcal{T}_K^{\mathbf{F}}$  and for every  $i \in \mathcal{P}$ :

$$\underline{a} \| \mathbf{x} \| \le V_{\mathbf{x},i} \le \overline{a} \| \mathbf{x} \| \tag{14}$$

- (C2) The second set of constraints is more involved. For every simplex  $\mathfrak{S}_{\nu} := \operatorname{co}\{\mathbf{0}, \mathbf{x}_{1}^{\nu}, \mathbf{x}_{2}^{\nu} \dots, \mathbf{x}_{n}^{\nu}\} \in \mathcal{T}_{K}^{\mathbf{F}}$ , we define the matrix  $X_{\nu} = (\mathbf{x}_{1}^{\nu} \mathbf{x}_{2}^{\nu} \cdots \mathbf{x}_{n}^{\nu})$ , i.e.  $\mathbf{x}_{k}^{\nu}$  is the *k*th column of  $X_{\nu}$ . Further, we define for every  $i \in \mathcal{P}$ , the vector of variables  $\mathbf{v}_{\nu,i} = (V_{\mathbf{x}_{1}^{\nu},i} V_{\mathbf{x}_{2}^{\nu},i} \cdots V_{\mathbf{x}_{n}^{\nu},i})^{\mathsf{T}}$ .
- The constraints are: for every simplex  $\mathfrak{S}_{\nu} \in \mathcal{T}_{K}^{\mathbf{F}}$ , for all  $j = 1, \ldots, n$  and all  $i \in \mathcal{P}$ :

$$\mathbf{v}_{\nu,i}^{\top} X_{\nu}^{-1} A_i \mathbf{x}_j^{\nu} \le -\alpha \|\mathbf{x}_j^{\nu}\|.$$
(15)

Note that these constraints are automatically fulfilled for j = 0, i.e.  $\mathbf{x}_{i}^{\nu} = \mathbf{0}$ .

(C3) The third set of constraints is: for every vertex **x** of a simplex in  $\mathcal{T}_{K}^{\mathbf{F}}$  and for every  $i, j \in \mathcal{P}$ ,

$$V_{\mathbf{x},j} \le \mu V_{\mathbf{x},i}.\tag{16}$$

#### 207 3.3. Solution to LP delivers lower bounds on dwell-time

In the previous subsection, we formulated an LP which basically specified the constraints in (8) at the vertices of the simplices contained in the triangulation. Here we prove that the feasibility of such a program provides us with piecewise linear Lyapunov functions for the individual subsystems over the entire state space that additionally fulfill (8c), thereby providing a lower bound on the average dwell-time.

Toward this end, assume that the LP problem in Section 3.2 has a solution with  $\alpha > 0$ . We then define the piecewise linear function  $V_i: \mathcal{D}_{\mathcal{T}_K^{\mathbf{F}}} \to \mathbb{R}$ , for every  $i \in \mathcal{P}$ , in the following way: • For every  $\mathbf{x} \in \mathcal{D}_{\mathcal{T}_{K}^{\mathbf{F}}}$  there exists a simplex  $\mathfrak{S}_{\nu} = \operatorname{co}\{\mathbf{0}, \mathbf{x}_{1}^{\nu}, \mathbf{x}_{2}^{\nu} \dots, \mathbf{x}_{n}^{\nu}\} \in \mathcal{T}_{K}^{\mathbf{F}}$ such that  $\mathbf{x} \in \mathfrak{S}_{\nu}$  and there exist a unique  $\lambda \in [0, 1]^{n}, \sum_{j=1}^{n} \lambda_{j} \leq 1$ , such that  $\mathbf{x} = \sum_{j=1}^{n} \lambda_{j} \mathbf{x}_{j}^{\nu}$ . We define

$$V_i(\mathbf{x}) = \sum_{j=1}^n \lambda_j V_{\mathbf{x}_j^\nu, i}$$

It is not difficult to see that the functions  $V_i$ ,  $i \in \mathcal{P}$ , are continuous functions that are linear on each simplex  $\mathfrak{S}_{\nu} \in \mathcal{T}_K^{\mathbf{F}}$ , in particular each  $V_i$  has the constant gradient  $\nabla V_{\nu,i} := \mathbf{v}_{\nu,i}^{\top} X_{\nu}^{-1}$  (row vector) on the interior of  $\mathfrak{S}_{\nu}$ , see e.g. [10, Rem. 9]. Hence, for any  $\mathbf{x} \in \mathfrak{S}_{\nu} \in \mathcal{T}_K^{\mathbf{F}}$ ,  $\mathbf{x} = \sum_{j=1}^n \lambda_j \mathbf{x}_j^{\nu}$ , we have for any  $i \in \mathcal{P}$  by (C1) and (C2) that

$$\nabla V_{\nu,i} \cdot A_i \mathbf{x} = \mathbf{v}_{\nu,i}^{\top} X_{\nu}^{-1} A_i \sum_{j=1}^n \lambda_j \mathbf{x}_j^{\nu} = \sum_{j=1}^n \lambda_j \mathbf{v}_{\nu}^{\top} X_{\nu}^{-1} A_i \mathbf{x}_j^{\nu}$$
$$\leq -\alpha \sum_{j=1}^n \lambda_j ||\mathbf{x}_j^{\nu}|| \leq -\frac{\alpha}{\overline{a}} \sum_{j=1}^n \lambda_j V_i(\mathbf{x}_j^{\nu})$$
$$= -\frac{\alpha}{\overline{a}} V_i(\sum_{j=1}^n \lambda_j \mathbf{x}_j^{\nu}) = -\frac{\alpha}{\overline{a}} V(\mathbf{x}).$$
(17)

Now, for any x in the interior of  $\mathcal{D}_{\mathcal{T}_{K}^{\mathbf{F}}}$ , we have that, for any  $i \in \mathcal{P}$ , there exists a simplex  $\mathfrak{S}_{\nu} \in \mathcal{T}_{K}^{\mathbf{F}}$  and an h > 0, such that

$$\mathbf{x} + [0, h] A_i \mathbf{x} \subset \mathfrak{S}_{\nu}$$

where  $\nu$  can depend on both x and *i*. Because  $V_i$  is linear on  $\mathfrak{S}_{\nu}$  we have

$$\limsup_{h \to 0+} \frac{V_i(\mathbf{x} + hA_i\mathbf{x}) - V_i(\mathbf{x})}{h} = \nabla V_{\nu,i} \cdot A_i \mathbf{x} \le -\frac{\alpha}{\overline{a}} V_i(\mathbf{x})$$

and since this holds true for all  $i \in \mathcal{P}$ , we have  $D^+V_i(\mathbf{x}, A_i\mathbf{x}) \leq -\frac{\alpha}{\overline{a}}V_i(\mathbf{x})$ . Since

$$V_i(\mathbf{x}) = \sum_{j=1}^n \lambda_j V_{\mathbf{x}_j^{\nu}, i} \ge \underline{a} \sum_{j=1}^n \lambda_j \|\mathbf{x}_j^{\nu}\| \ge \underline{a} \|\mathbf{x}\|$$

by the constraints (C1), and for all  $i, k \in \mathcal{P}$ ,

$$V_i(\mathbf{x}) = \sum_{j=0}^n \lambda_j V_{\mathbf{x}_j^{\nu}, i} \le \sum_{j=0}^n \lambda_j \mu V_{\mathbf{x}_j^{\nu}, k} = \mu V_k(\mathbf{x}),$$

it is clear that the  $V_i$  fulfill the constraints (8) in the interior of  $\mathcal{D}_{\mathcal{T}_K^{\mathbf{F}}}$ . Just define

$$\overline{a}' := \max_{\|\mathbf{x}\|=1} \max_{i=1,2,\dots,N} V_i(\mathbf{x})$$

and we have

$$\underline{a} \|\mathbf{x}\| \le V_i(\mathbf{x}) \le \overline{a}' \|\mathbf{x}\|,$$
$$D^+ V_i(\mathbf{x}, A_i \mathbf{x}) \le -\frac{\alpha}{\overline{a}} V_i(\mathbf{x})$$

for all x in the interior of  $\mathcal{D}_{\mathcal{T}_{K}^{\mathbf{F}}}$ . Note that we proved (17) directly from the constraints and did not go through constraints (8) with  $\overline{a} = \overline{a}'$ , which would lead to a worse estimate on  $\tau_{a}$ .

By extending  $V_i$  to  $\mathbb{R}^n$  in the obvious way, i.e. for every  $\mathbf{x} \in \mathbb{R}^n$  there exists a  $\mathfrak{S}_{\nu}$  and unique numbers  $\lambda_j \geq 0$  such that  $\mathbf{x} = \sum_{j=1}^n \lambda_j \mathbf{x}_j^{\nu}$  (a cone defined by the vertices of  $\mathfrak{S}_{\nu}$ ) and we set  $V_i(\mathbf{x}) = \sum_{j=1}^n \lambda_j V_{\mathbf{x}_j^{\nu},i}$ , we see that the  $V_i$  fulfill the constraints (8) on  $\mathbb{R}^n$ , for each  $i \in \mathcal{P}$ .

### **4.** Simulations

We will now test our LP algorithm for several examples from the literature. The class of systems for these simulations is (13). The set  $\mathcal{P}$  and the matrices  $\{A_i\}_{i\in\mathcal{P}}$  will be specified differently for the examples considered here. In the examples, we always fix  $\underline{a} = 10^{-5}$  and  $\overline{a} = 10$ . We used YALMIP/sdpt3 and Gurobi to solve the LMI and LP problems, respectively.

# 4.1. Example 1: Dwell-time stable but not under arbitrary switchingConsider the switched system (13) with

$$A_1 = \begin{pmatrix} -0.1 & -1 \\ 2 & -0.1 \end{pmatrix}, \quad A_2 = \begin{pmatrix} -0.1 & -2 \\ 1 & -0.1 \end{pmatrix}$$

This example is taken from [16, p. 26]. It is stable for a certain minimum value 234 for the average dwell-time, but it is not stable under arbitrary switching. Solving 235 (10) using the LMI approach, the best  $\tau_a$  obtained is 5.1929 with  $\mu = 2$ . Using the 236 LP approach, the best  $\tau_a$  obtained is 4.5283 with  $\mu = 1.4$  and using K = 500 in 237 the triangulation. Using triangulations with fewer triangles delivers a higher lower 238 bound  $\tau_a$  for the average dwell time; K = 50 gives  $\tau_a = 5.16493$  with  $\mu = 1.45$ , 239 K = 100 gives  $\tau_a = 4.79315$  with  $\mu = 1.4$ , and K = 200 gives  $\tau_a = 4.62407$ 240 with  $\mu = 1.4$ . In all cases they are better than the bounds from the LMI approach. 241 242



Figure 2: Plots for  $\mu$  versus  $\tau_a$  in Example 1.



Figure 3: LMI based plot for  $\mu$  vs  $\tau_a$  in Example 2.

# 4.2. Example 2: Stable under arbitrary switching but no common quadratic Lya punov function

Take  $\mathcal{P} = \{1, 2\}$ , with the matrices

$$A_1 = \begin{pmatrix} -1 & -1 \\ 1 & -1 \end{pmatrix}, \quad A_2 = \begin{pmatrix} -1 & -10 \\ 0.1 & -1 \end{pmatrix}$$

This example is taken from [6]. It is stable under arbitrary switching but the matrices  $A_1$  and  $A_2$  do not share a common quadratic Lyapunov function. This example helps us see the limitation of using LMIs because searching for quadratic certificates in this case is not the best choice.

Solving (10) using LMIs, the minimum value for  $\tau_a$  is  $\tau_a = 17.0394$  with  $\mu = 3.1$ . Whereas, with our LP approach, K = 20 gives a solution with  $\mu =$ 1. Hence, the origin is stable under arbitrary switching ( $\tau_a = 0$ ), and we get a common piecewise linear Lyapunov function although no quadratic Lyapunov function exists.

## 4.3. Example 3: Exponentially stable system under arbitrary switching with 5 modes

We consider the switched system (13) with  $\mathcal{P} = \{1, 2, 3, 4, 5\}$ , where

$$A_{1} = \begin{pmatrix} -5 & 1 & 2 \\ 0 & -5 & 1 \\ 0 & 1 & -2 \end{pmatrix}, \quad A_{2} = \begin{pmatrix} -1 & 3 & 1 \\ 0 & -2 & 0 \\ 0 & 1 & -1 \end{pmatrix},$$
$$A_{3} = \begin{pmatrix} 0 & 0 & 3 \\ -2 & -1 & -3 \\ -1 & 0 & -2 \end{pmatrix}, \quad A_{4} = \begin{pmatrix} -4 & 0 & -3 \\ 2 & -2 & 4 \\ 1 & 0 & -1 \end{pmatrix},$$
$$A_{5} = \begin{pmatrix} -1 & 0 & 0 \\ -1 & -1 & -1 \\ -3 & 0 & -4 \end{pmatrix}$$

This example was also considered in [17] with a graph that determines the switching sequence, and in this particular, we have the star topology. With K = 6, we get a solution with  $\mu = 1$ , i.e. the origin is exponentially stable under arbitrary switching (which is then arbitrary without the graph too).

With the LMI approach in (10), the minimum value for the average dwell-time is  $\tau_a = 4.6870$  with  $\mu = 2.7$ .

262



Figure 4: LMI based plot for  $\mu$  vs  $\tau_a$  in Example 3.

## 263 5. Conclusions

We considered a linear programming (LP) based computational algorithm for computing lower bounds on average dwell-times that ensure asymptotic stability of switched systems. The algorithm is essentially based on gridding the state space into simplices and computing values for the corresponding Lyapunov functions at the vertices of these simplices. By choosing appropriate values of the parameters in the inequalities defining the linear program, the solution provides

us lower bounds on the average dwell-time necessary to assure stability. From the 270 simulations, we see in several case studies, that LP based bounds are better than 271 the ones based on linear matrix inequalities (LMIs). This is not really surprising 272 since LMIs restrict the Lyapunov functions to be quadratic, whereas the proposed 273 LPs can potentially approximate a broader class of Lyapunov function templates. 274 Computing dwell-time via inequalities in (8) introduces some conservatism be-275 cause we optimize over a single parameter  $\alpha$  while keeping  $\mu$  fixed. The same 276 conservatism is observed in going from (6) to (10). As a topic of ongoing investi-277 gation, we are working out algorithm to optimize  $\alpha$  and  $\mu$  simultaneously directly 278 using an LP version of (6). Other than understanding the complexity of the pro-279 posed algorithm, we also aim to study the extensions of the proposed algorithm 280 in different directions, which includes the study of generalized lower bounds on 281 average dwell-time [15, 18]. 282

### **283** References

- [1] A. A. Ahmadi, R. M. Jungers, P. A. Parrilo, and M. Roozbehani. Joint spectral radius and path-complete graph Lyapunov functions. *SIAM Journal on Control and Optimization*, 52(1):687–717, 2014.
- [2] S. Albertsson, P. Giesl, S. Gudmundsson, and S. Hafstein. Simplicial complex with approximate rotational symmetry: A general class of simplicial complexes. *J. Comput. Appl. Math.*, 363:413–425, 2020.
- [3] R. Baier, L. Grüne, and S. Hafstein. Linear programming based Lyapunov
   function computation for differential inclusions. *Discrete Contin. Dyn. Syst. Ser. B*, 17(1):33–56, 2012.
- [4] C. Briat. Convex conditions for robust stabilization of uncertain switched
   systems with guaranteed minimum and mode-dependent dwell-time. *Systems and Control Letters*, 78:63 72, 2015.
- [5] S. Dashkovskiy and A. Mironchenko. Input-to-state stability of nonlinear
   impulsive systems. *SIAM J. Control & Optimization*, 51(3):1962 1987, 2013.
- [6] W.P. Dayawansa and C.F. Martin. A converse Lyapunov theorem for a class
   of dynamical systems which undergo switching. *IEEE Transactions on Au- tomatic Control*, 44(4):751–760, 1999.

- J. P. Geromel and P. Colaneri. Stability and stabilization of continuous time switched linear systems. *SIAM Journal on Control and Optimization*,
   45(5):1915–1930, 2006.
- [8] P. Giesl and S. Hafstein. Implementation of a fan-like triangulation for the
   CPA method to compute Lyapunov functions. In *Proceedings of the 2014 American Control Conference*, pages 2989–2994 (no. 0202), Portland (OR),
   USA, 2014.

[9] P. Giesl and S. Hafstein. Implementation of a simplicial fan triangulation
 for the CPA method to compute Lyapunov functions. In *Proceedings of the* 2014 American Control Conference, Portland (OR), USA, no. 0202, pages
 2989–2994. IEEE, 2014.

- <sup>313</sup> [10] P. Giesl and S. Hafstein. Revised CPA method to compute Lyapunov func-<sup>314</sup> tions for nonlinear systems. *J. Math. Anal. Appl.*, 410:292–306, 2014.
- <sup>315</sup> [11] P. Giesl and S. Hafstein. Review of computational methods for Lyapunov <sup>316</sup> functions. *Discrete Contin. Dyn. Syst. Ser. B*, 20(8):2291–2331, 2015.
- [12] S. Hafstein. Implementation of simplicial complexes for CPA functions in C++11 using the Armadillo linear algebra library. In *Proceedings of the 3rd International Conference on Simulation and Modeling Methodologies, Technologies and Applications (SIMULTECH)*, pages 49–57, Reykjavik, Iceland, 2013.
- [13] S. Hafstein. *Informatics in Control, Automation and Robotics*, volume 793
   of *Lecture Notes in Electrical Engineering*, chapter Sliding Modes and Lya punov Functions for Differential Inclusions by Linear Programming, pages
   584–606. Springer, 2022.
- I4] J.P. Hespanha and A.S. Morse. Stability of switched systems with average dwell-time. In *38th IEEE Conf. on Decision and Control (CDC)*, pages 2655–2660, 1999.
- [15] A. Kundu, D. Chatterjee, and D. Liberzon. Generalized switching signals for
   input-to-state stability of switched systems. *Automatica*, 64:270–277, 2016.
- [16] D. Liberzon. *Switching in systems and control*. Systems & Control: Foun dations & Applications. Birkhäuser, 2003.

- [17] S. Liu, S. Martínez, and J. Cortés. Average dwell-time minimization of
   switched systems via sequential convex programming. *IEEE Contr. Syst. Lett.*, 6:1076–1081, 2021.
- [18] S. Liu, A. Tanwani, and D. Liberzon. ISS and integral-ISS of switched
   systems with nonlinear supply functions. *Mathematics of Controls, Signals, and Systems*, 34(2):297–327, 2022.
- [19] S. Marinósson. Lyapunov function construction for ordinary differential
   equations with linear programming. *Dynamical Systems: An International Journal*, 17:137–150, 2002.
- [20] S. Mitra, N. Lynch, and D. Liberzon. Verifying average dwell time by solv ing optimization problems. In *Proceedings of 19th Intl. Workshop on Hybrid Systems: Computation and Control*, pages 476 490, 2006.
- [21] A. S. Morse. Supervisory control of families of linear set-point con trollers Part I. exact matching. *IEEE Transactions on Automatic Control*,
   41(10):1413–1431, 1996.
- M. Della Rossa, M. Pasquini, and D. Angeli. Continuous-time switched systems with switching frequency constraints: Path-complete stability criteria.
   *Automatica*, 137:110099, 2022.
- <sup>351</sup> [23] M. Della Rossa and A. Tanwani. Instability of dwell-time constrained <sup>352</sup> switched nonlinear systems. *Systems & Control Letters*, 162:105164, 2022.
- [24] A.M. Samoilenko and N.A. Perestyuk. *Impulsive Differential Equations*.
   World Scientific Publishing, 1995.
- R. Shorten, F. Wirth, O. Mason, K. Wulff, and C. King. Stability criteria for
   switched and hybrid systems. *SIAM Review*, 49(4):545–592, 2007.