



HAL
open science

Impact of source modeling and poroelastic models on numerical modeling of unconsolidated granular media: application at the laboratory scale

Kassem Asfour, Roland Martin, Didier El Baz, Ludovic Bodet, Bastien Plazolles

► To cite this version:

Kassem Asfour, Roland Martin, Didier El Baz, Ludovic Bodet, Bastien Plazolles. Impact of source modeling and poroelastic models on numerical modeling of unconsolidated granular media: application at the laboratory scale. *Surveys in Geophysics*, inPress, 10.1007/s10712-023-09812-w . hal-04255458

HAL Id: hal-04255458

<https://laas.hal.science/hal-04255458>

Submitted on 24 Oct 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Impact of source modeling and poroelastic models on numerical modeling of unconsolidated granular media: application at the laboratory scale

K. Asfour¹ R. Martin¹ D. El Baz² L. Bodet³
B. Plazolles¹

the date of receipt and acceptance should be inserted later

Abstract The near surface is characterized by using different numerical techniques, among them seismic techniques which are non-destructive. More particularly, for a better understanding of acoustic and seismic measurements in unconsolidated granular media that can constitute the near surface, many studies have been conducted in situ and also at the laboratory scale where theoretical models have been developed. In this article, we want to model such granular media that are difficult to characterize. At the laboratory scale, dry granular media can be modeled with a homogenized power-law elastic model that depends on depth. In this context, we validate numerically a similar power-law elastic model for such media by applying it to a homogenized elastic medium or to the solid frame of a poroelastic medium that consists of solid and air components. By comparing the response of both rheologies, we want to highlight what poroelastic media can bring to better reproduce the experimental data in the time and frequency domains. To achieve this objective, we revisit studies carried out on unconsolidated granular media at the laboratory scale and we compare different models with different rheologies (elastic or poro-elastic), dimensions (2D or 3D), boundary conditions (PML or Dirichlet) and locations of the source (modelled as a vibratory stick or a point force) in order to reproduce the experimental data. We show here that a poroelastic model describes better the amplitudes of the seismograms. Furthermore, we study the sensitivity of the seismic data to the source location which is crucial to improve the amplitude of the signals and the detection of the different seismic modes.

Keywords Porous and granular media, wave propagation, numerical modeling, dispersion analysis, surface waves.

¹ Laboratoire GET, Université Toulouse 3 Paul Sabatier, IRD, CNRS UMR 5563, 31400 Toulouse, France email: Kassem.Asfour@hotmail.com, roland.martin@get.omp.eu, bastien.plazolles@get.omp.eu

² LAAS-CNRS, Université de Toulouse, UPR 8001, 31031, Toulouse, France. email: elbaz@laas.fr

³ Sorbonne Université, CNRS, EPHE, UMR 7619 METIS, 75252 Paris Cedex 5, France. email: ludovic.bodet@sorbonne-universite.fr

1 Introduction

A natural medium can be composed of unconsolidated materials such as clay, silt, sand, gravel or materials derived from the erosion of rocks. It is thus important to characterize media made of these materials to better understand acoustic and seismic measurements in such soils and their related geological environments. This point is particularly important in the case of near surface studies which feature complex environment that can contain natural resources such as water, gas, hydrocarbons. More generally, it is interesting to study the near surface because it is the place of fluid exchanges and life activities as well as the interface for earth-atmosphere coupling.

Many studies on elastic wave velocities in unconsolidated materials have been conducted in situ and at the laboratory scale and theoretical models have been proposed. In particular, in the case of granular media studies, new theoretical and numerical models have been designed those last years for acoustic characterization and response studies of meta-materials, porous and granular media at the laboratory scale by Palermo et al. (2018); Zaccherini et al. (2020); Pu et al. (2020). Among the seismic techniques used to determine the physical properties of such media, we can cite the tomography techniques which are based on minimising the first arrival times residuals (Zelt and Smith, 1992; Le Meur, 1994; Improta et al., 2002; Ravaut, 2003) or the MASW (Multiple Analysis of Surface Waves) technique (Nazarian and Stokoe, 1984; Ganji et al., 1997; Park and Elrick, 1998; Xia et al., 1999; Foti, 2000; Bitri et al., 2002; Xia, 2014) which studies the surface wave dispersion. Toolboxes like SWIP (Surface-Wave Inversion and Profiling method), presented in (Pasquet and Bodet, 2017), can be used to estimate the S -shear wave velocities (V_s) of such media. Some common resulting models proposed at the near surface scale show an important increase in P and S wave velocity as a function of depth. Indeed, based on Hertz–Mindlin contact theory (in the context of inter-grain forces modeling), the velocity structure of such media can be modelled as (Gassmann, 1951): $V_{p,s} = \gamma_{p,s}(\rho g z)^{\alpha_{p,s}}$, where g is the gravity acceleration, ρ is the bulk density of grains or glass beads, $\gamma_{p,s}$ is a depth-independent coefficient which mainly depends on the elastic properties of the grains, porosity and coordination number of the packed structure, and $\alpha_{p,s}$ is the power-law exponent. The parameter $\alpha_{p,s}$ depends on the grain dispersion, grain disorder, grain contacts and the form of grains (Makse et al., 1999; Zimmer et al., 2007; Tournat and Gusev, 2010; Schön, 2015). In those studies, similar power-law profiles of seismic wave velocities have been investigated. This power-law exponent is generally close to 1/6 for random close packing of uniform spheres. A similar exponent value has been proposed by Bachrach et al. (1998) for a shallow sand medium in situ. However, in real materials strong contact disorders between grains can be present due to low degrees of heterogeneity in grain sizes or sphericity, and then this exponent coefficient can be different from 1/6. This exponent is not only dependent on the dispersion of grain size or grain sphericity but it depends also strongly on the confinement pressure of the medium. In many experiments, this exponent can be increased for lower static pressures applied to the medium (0.1 - 200 KPa) and can reach values from 1/6 up to 1/4.

In this context, before characterizing any (partially or fully) saturated media with fluid (water, gas), we want to model correctly the seismic wave propagation in unconsolidated granular media in the dry regime. In particular, we revisit

here the study in [Bodet et al. \(2014\)](#) at the laboratory scale for granular media (made of glass beads) that are submitted to low pressures and do not contain any fluid. The physical model deduced is a power-law model with $\alpha_{p,s}$ close to $\frac{1}{3}$, which is a typical value that can be reached in the experiments in the case of very low pressures (less than 0.1 kPa). Besides, for this range of low pressures, similar exponent coefficients have been obtained in other acoustic experiments by ([Jacob et al., 2008](#); [Tournat and Gusev, 2010](#)). However, we want here to perform a deeper acoustic signal analysis in this context for different numerical designs in 3D and 2D to accelerate the computations and to model the relevant signals without noise and without reflections contaminating the computational domain. More particularly, we compare different rheological (elastic or poroelastic) models involving our power-law and we investigate their ability to better reproduce the seismograms and phase dispersion diagrams for the granular medium under study. On the medium/long term, all the methodology used here could be applied at the laboratory scale and also to data collected at near-surface field (in-situ) scales.

The main objective of this study is to numerically validate the models considered by verifying whether they allow us to better interpret the data recorded in the laboratory. In order to do this, numerical simulations are run to fully replicate the configuration of the laboratory experiments. The physical problem consists in solving the seismic wave equation for different rheologies (pure elastic, poroelastic) in dry regime in order to determine which of them best explains the laboratory data. Besides, in a previous work ([Bodet et al., 2014](#)) significant differences in amplitude between the experimental and simulated waveforms were exhibited and we thus identified two main issues to address in order to better model physically and numerically this kind of complex granular medium:

- Finding a more adequate rheological law (elastic or poroelastic) describing the mechanical behavior of the medium.
- Studying the impact of the type of source wavelet on the computed data by modelling the source as a vibratory stick like in the experiment of [Bodet et al. \(2014\)](#) or as a virtual point source located at different depths.

Indeed, the choice of the rheological law and the source model influence the waveforms and the amplitudes as well as the different surface and P modes in the dispersion diagrams. This will be discussed in the following sections of this study.

First, to simulate such media, 3D numerical elastic wave propagation simulations are performed in the case of a pure elastic medium. The calculated solutions are then compared with experimental data recorded at the laboratory scale. Time and frequency (dispersion) analyses are done to compare respectively the first arrivals and the dispersion curves of the experimental data with the simulated ones.

Second, since the physical model considered is vertically stratified and invariant in the direction orthogonal to the vertical plane containing the source and the line of receivers, we can reduce the 3D model to a 2D one. The 2D calculated seismograms can reproduce the 3D ones by introducing a source-receiver distance rescaling of the real data seismograms following a similar approach as in [Forbriger et al. \(2014\)](#). Besides, the 2D computations allow us also to accelerate even more the calculations. The introduction of the 2D calculations is relevant because the source injects the maximum of energy into the vertical plane it belongs to and the model is invariant in the orthogonal direction. Furthermore, since the 3D waves

are attenuated due to the geometrical divergence and since the vertical walls of the experimental box are far enough from the seismic line, the only significant acoustic reflections are coming from the bottom of the box. This is another reason of performing 2D simulations in the vertical plane. Therefore, we study different configurations in 3D and 2D with a free surface on top and compare the results to the real data. In some cases we apply efficient PML absorbing boundary conditions to all vertical walls in presence or not of Dirichlet conditions at the bottom. The introduction of the PMLs allows us to truncate the computational domain and to also reduce the computing time while reproducing the experimental data and keeping the relevant acoustic phases and modes we are interested in.

Third, we make the rheology more complex (porous medium using a Biot poroelastic model for instance) in 2D to compare it to the homogenized elastic medium and to the experimental results.

Comparisons between simulated and experimental data are done in two domains:

- Time domain: we detect the first travel-time arrivals of the seismic waves.
- Frequency domain: we calculate the dispersion curves using a slant-stack transform.

The choice of the numerical tools was made taking into account four main criteria: accuracy, performance, simplicity of the method, and the nature of the physical problem to be solved. A 3D finite difference code, fourth-order in space and second-order in time, called UNISOLVER (updated version of the 3D SEISMIC_CPML code, (Komatitsch and Martin, 2007; Martin and Komatitsch, 2009; Martin et al., 2010)) is used here to solve the wave equations in a stratified elastic medium taking into account different models and computational configurations involving strong depth gradient velocities. The fourth-order finite difference discretization in space is a good choice because in the case of a flat topography, it is sufficiently accurate, easy to implement and faster than other numerical methods. Mirror conditions are implemented at the free surface. With this type of boundary conditions, the numerical solution is sufficiently accurate at the free surface and in the inner computational domain. For more details, the reader is referred to the work on fourth-order finite differences of Graves (1996) and (Moczo et al., 1997, 2010, 2001) for 3D elastic and viscoelastic modelling respectively. Optimized Perfectly Matched Layer/PML absorbing (Komatitsch and Martin, 2007; Martin et al., 2008b) and free surface conditions are implemented and validated by comparing with reference codes such as SPECFEM (spectral finite elements (Komatitsch, 1997)) which is commonly used in the geophysical community. UNISOLVER is parallelized and therefore the computation time is reduced which makes it very efficient for the realization of our numerical simulations. In the present study we extend the discretization to the 2D and 3D poroelastic media (see also Bodet et al. (2014)). 2D versions of this code for both elastic and porous media are also used to highlight the contribution of the porous medium to the elastic medium, and also the ability of the poroelastic model to better reproduce the acoustic modes in the frequency domain.

The structure of this study is summarized as follows. Section 2 deals with the experimental setup and the physical homogenized elastic model obtained by inversion of first arrivals and dispersion diagrams. In section 3, the numerical setup for the different rheological models is given. In sections 4 and 5, qualitative (seismograms, spectrograms and dispersion images) and quantitative (first arrivals,

dispersion curves) analysis are done on the different numerical models considered, respectively. In section 6, we consider different locations of the numerically modeled sources to show the influence of the choice of the source location at depth on the detection of the different seismic modes. Finally, the results obtained are discussed. In section 7, conclusions, recommendations and future work are presented.

2 Experimental setup and physical model

2.1 Experimental setup

In this paper, we are interested in experiments on unconsolidated granular media which are carried out at the laboratory scale (see Bodet et al. (2014)). The studied physical medium has a length of 1 m, a height of 0.22 m and a width of 0.8 m. The box is filled with 180-300 μm diameter glass beads (GB1) and the bottom of the box consists of a metallic sieve glued on a perforated plate (see Figure 1). The deposition process has been done experimentally to ensure a homogeneous distribution of the glass beads. The bulk density has been measured many times during the deposition process, and it was always estimated in a range between 1600 and 1610 kg/m^3 . We thus make the choice to consider a density value of 1610 kg/m^3 for the bulk density ρ_{GB1} which is the most representative, and its corresponding porosity is $\Phi_{GB1} = 0.356$.

The source consists of a metal stick connected to a waveform generator (see Figure 2) with a dominant frequency $f_0 = 1500 \text{ Hz}$. The latter is injected in the vertical yOz -plane with a tilted angle of 20° with the vertical normal to the free surface.

For a given source location, the normal component of the particle velocity (V_z) is recorded in time at the surface of the medium as a “seismogram” using an oscilloscope. Up to 100 traces were recorded (using an oscilloscope) with a sampling rate of 10^{-5}s (0.01ms) over a time series length of 50 ms in linear single-channel walkway mode along the Oy direction.

2.2 Experimental data

The experimental data at our disposal have been recorded at 25 receivers placed linearly and equidistantly at the surface of the medium. For a given source location, the normal component of the particle velocity (V_z) is recorded in time at the surface of the medium as a “seismogram” using an oscilloscope at a sampling time rate of 0.01ms. From the source over a length of 0.5 m in the y -direction, the spacing between the receivers is 0.02 m.

We underline that here the data are not normalized data. However, if the data are normalized with respect to the maximum of the signals measured over all receivers, then source ringing effects appear at the source location and also at near off-set as observed in Jacob et al. (2008); Bodet et al. (2010); Bergamo et al. (2014); Bodet et al. (2014). According to these authors, it is very hard to remove them. A better design of the contact between the source and the beads should be




Fig. 1. (a) Physical model (PM) in Bodet et al. (2014): a granular layer 180–300 $\times 10^{-6}$ m diameter GBs (GB1) sieved into a $(1000 \times 800 \times 220)$. 10^{-3} m box. The bottom of the box consisted of a metallic sieve (dashed lines) glued on a perforated plate. The PM HOM22 was prepared by sieving GB1 directly onto the metallic sieve. We consider a density value of 1610 kg/m^3 for the bulk density ρ_{GB1} which is the most representative. This value led to a porosity of $\Phi_{GB1} = 0.356$. $(x_s, y_s) = (0.4\text{m}, 0.25\text{m})$ are the source location coordinates (marked by a red star at 25 cm from left wall), and the dashed light blue line shows the data recording line (50cm long from the source) and acquisition parameters. (b) The power law model for the dry unconsolidated granular medium case (zero over-pressure) using parameters $\alpha_{p,s}$ and $\gamma_{p,s}$ estimated by simulated annealing-based inversion of the measured first arrival times for V_p and of the dispersion curve related to the fundamental (Rayleigh) mode for V_s extracted from the dispersion diagrams.

proposed to reduce or eliminate those effects. In the following sections, we thus concentrate our analysis on the main relevant signal. To reduce the source effects and noise, we consider the receivers located 5 cm away from the source and we filter the data with a Butterworth band-pass filter in the 100–3000 Hz frequency band since the signal amplitude is maximal in this window, as shown in Figure 3. Besides, in Figure 3-c the difference between non filtered and filtered data exhibit some small noise effects close to the source due to the ringing effects mentioned before. In Figure 4, we show the seismograms of V_z component (filtered and not filtered) at receivers 10, 15 and 20 located at 20, 30 and 40 cm from the source, respectively. In Figures 3 and 4 the non-filtered and filtered data are both showing the same acoustic phases in presence of noise or not, and their difference only shows some coherent noise. In the following sections we will thus only compare solutions with filtered real data.

Due to the fact that we aim at studying 2D seismograms because 1) the model is vertically 2D and invariant according to the direction orthogonal to the vertical plane, and 2) the 2D cases are much faster to compute than the 3D case, it is crucial to transform the real data from 3D to 2D and to model the source in the synthetic cases for the current model under study. In the close vicinity of the source, the wavefield transformation from 3D to 2D scales as $\sqrt{rV_{ph}}$ where r is




Fig. 2. The force source signal is sent from a waveform generator to a low frequency (LF) shaker exciting a 120 mm metal stick buried in the granular material over a 15mm length. The laser beam is set at the zero-offset position (0.25 m in the length direction) to record the vertical component of velocity V_z of the stick (the red line in the right inset). (a) Source signal spectrum centered around 1500 Hz; (b) detail of vibrator source and source signal configuration.

the offset and V_{ph} is the phase velocity. But for larger offsets r from the source, the medium is dispersive and the amplitude of the signals is scaling as r/\sqrt{t} . In a given frequency band, the real data seismograms are convolved with $1/\sqrt{t}$ and are scaled respect to the offset as previously mentioned and proposed by Schäfer et al. (2012); Groos et al. (2013, 2014a) and also very well synthetised in Forbriger et al. (2014). Those corrections have been applied efficiently in near surface applications in the context of full waveform inversion in presence or not of attenuation as in Schäfer et al. (2013, 2014); Groos et al. (2014b).

2.3 Physical model

We are interested in a V_p/V_s model obtained from the experiment on an unconsolidated granular medium as in Bodet et al. (2014). The latter is deduced by ray tracing-based travel time inversion for the V_p model and phase velocity diagram inversion for the V_s model. Those inverted V_p and V_s models are given by a power




Fig. 3. Experimental data not filtered (a) and filtered (b) , as well as their difference (c). Time is given in seconds.

law dependent on hydrostatic pressure as proposed in Gassmann (1951) (Figure 1-b):

$$V_p = \gamma_p (\rho g h)^{\alpha_p} \quad (1a)$$

$$V_s = \gamma_s (\rho g h)^{\alpha_s} \quad (1b)$$

where ρ , g and h are respectively the density, the gravitational acceleration at Earth surface ($g = 9.81 \text{ m.s}^{-2}$) and the depth of the medium. The parameters

γ and α for the dry case are estimated by simulated annealing-based inversion of the measured first arrival times for V_p and of the dispersion curve related to the fundamental (Rayleigh) mode for V_s . Those inverted γ and α parameters have the following values: $\alpha_p = 0.3$, $\gamma_p = 21$, $\alpha_s = 0.33$ and $\gamma_s = 8.2$ (see [Bodet et al. \(2014\)](#)).

In ([Bodet et al., 2014](#)), this model was partially validated numerically using a 3D elastic finite difference code. But there was still a problem in reproducing the amplitudes of higher modes. In the seismograms as well as in the velocity phase dispersion diagrams, the computed amplitudes were too high when compared to the real data. To mitigate this drawback, first, we reproduce the results of [Bodet et al. \(2014\)](#) with our 3D finite difference code UNISOLVER. Secondly, we reduce the 3D model to a 2D model to accelerate the computations and finally we integrate the V_p/V_s model into a 2D poro-elastic model according to the Biot poro-elastic model ([Biot, 1956a](#)) which makes the assumption of interconnected pores between grains and enables to describe and take into account medium wavelengths of the 2 component porous medium. One of the main goals is to increase the complexity of the rheologies to better reproduce the amplitudes of higher modes.

3 Numerical setup

We consider the following three models (the reader is referred to appendices [A](#), [B](#) and [C](#) for elastic and poroelastic equations):

- 3D elastic: we use UNISOLVER (our finite difference/FD code which is fourth-order in space and second-order in time) ([Komatitsch and Martin, 2007](#)) to reproduce the results of [Bodet et al. \(2014\)](#).
- 2D elastic: we reduce the 3D model to the vertical plane where the metal stick is located. In this case, we use our FD code seismic-CPML-elastic (fourth-order in space and second-order in time) ([Komatitsch and Martin, 2007](#)) and we compare the results to the experimental data.
- 2D poro-elastic: poroelastic materials are most of the time modelled using the Biot theory ([Biot, 1956a,b](#)). In this study, we choose to remain in the context of Biot models. Thus, we take into account parameters such as porosity, permeability, viscosity and tortuosity (measured during the experiment). The compressional P wave velocities (fast and slow) and the effective shear S wave velocities in the porous medium depend also on the P and S elastic wave velocities of the solid frame that is modelled in our present study using equation (1). A version of Seismic-CPML for Biot model is used ([Martin et al., 2008b](#)).

For each model, we consider three cases corresponding to three different types of boundary conditions:

- (Case 1) Dirichlet: in this case, all the boundaries except the free surface are Dirichlet boundary conditions (i.e, particle velocities equal to zero); Dirichlet conditions are defined to simulate a rigid material on the five other sides of the box in 3D, and on the three other sides in 2D.
- (Case 2) PMLs: in this case, we consider absorbing boundary conditions (C-PMLs) on all the boundaries except the free surface and the bottom boundary where a Dirichlet condition is applied. The PMLs allow to absorb the outgoing waves to mimic an open medium.

- (Case 3) Full PMLs: in this case, on all the boundaries except the free surface, absorbing boundary conditions (C-PMLs) are considered.

In all cases, the free surface condition is implemented at the top of the computational domain using the zero normal traction assumption for the different cases.

For the different models and cases, the force source signal (see Figures 5 and 6) is injected all along the metal stick. The latter is simulated numerically by injecting the time wavelet source signal over a series of points located along the stick.

3.1 3D/2D elastic models

The physical model has a width of 0.35 m , a length of 1 m and a height of 0.215 m . The density is given by $\rho = 1610 \text{ Kg}/m^3$.

In 3D, we consider a uniform mesh such that $\Delta X = \Delta Y = \Delta Z = 5 \cdot 10^{-4} m$ and composed of $70 \times 2000 \times 430$ points. The total number of points of the mesh is 60,2 millions points. The time step used is $\Delta t = 10^{-6} s$ and the total number of time steps is 50000 corresponding to 50 ms (time period of the experiment). In this case, the Courant–Friedrichs–Lewy/CFL stability number is equal to 0.6. In our simulations, the injected source is the real (experiment) source time wavelet (sampling rate of $10^{-5} s$) interpolated at the simulation time step Δt . The spectrum of the source is centered around a dominant frequency of 1500 Hz (see Figure 2-a).

PML layers are composed of 15 points for efficient boundary absorption. The V_p and V_s modeled velocities are invariant in the direction orthogonal to the vertical plane and follow the power-law trend with depth (see Figure 1-b). The velocity profiles, continuous in theory, are discretized according to the spacing discretization ΔZ in depth.

The receivers are spaced every $5 \cdot 10^{-3} m$ (10 grid points) at the free surface to record the seismograms of the normal component of the particle velocity (see Figure 5).

We reduce the 3D model to a 2D model by considering only the vertical plane where the metal stick (source) is located.

In order to obtain amplitudes and waveforms of the recorded signals as close as possible to the experimental data, we simulate different configurations using the 3D parallel FD code UNISOLVER (we refer the reader to appendix D for code performance details): with Dirichlet (case 1), PMLs (case 2, just at the four vertical outer boundary walls and Dirichlet at the bottom) or Full PMLs (case 3, PML layers everywhere) conditions except at the free surface. In the 2D case, we consider the same configurations mentioned above and we also use the 2D code seismic_CPML_elastic.

3.2 2D poroelastic model

In the poro-elastic case (see appendix C for the Biot model used here), one considers the same discretization in space and time as in the elastic cases. The length

and width of the box are also preserved.

In our simulation, the solid components are glass beads and the fluid considered is the air. The density of the solid $\rho_s = 2500 \text{ Kg/m}^3$ and the density of the fluid $\rho_f = 1.20 \text{ Kg/m}^3$ give an apparent density $\rho_w = 6,46 \text{ Kg/m}^3$ and a density of the saturated medium $\rho = 1610 \text{ Kg/m}^3$ (using relations in the Biot model). The porosity, the permeability, the viscosity and tortuosity are given by $\Phi_{GB} = 0.356$, $\mathcal{K} = 9.510^{-11} \text{ m}^2$, $\nu = 1.907 \cdot 10^{-5} \text{ Pa.s}$ and $a = 1.91$, respectively.

The bulk modulus of air is 0.101 MPa and the bulk modulus of the solid and saturated medium are computed depending on the variation of P-wave and S-wave velocities which affect the effective Lamé parameters λ and μ of the porous medium and λ_s of the solid frame (see Figure 7 for the different velocities computed with this model). Seismic velocities V_s and V_p characterize the pure elastic model, while V_s , V_{pFAST} and V_{pSLOW} characterize the porous medium. The difference between the poroelastic and elastic V_s velocities is very small and is thus multiplied by 10^3 to see it more clearly. S-wave velocity is similar for both the elastic and the poro-elastic models because the fluid represented by the air presents very low shear-stress compared to the solid frame or even no-shear stress (as any other fluid). Its contribution is thus introduced essentially through the bulk compressional stress. Therefore, the fluid is essentially contributing to pressure and V_p (fast and slow) velocities. We use seismic_CPML_poroelastic, a FD code (fourth-order in space and second-order in time) to resolve the 2D Biot model in the different boundary cases considered.

When we calculate the maximum frequency of the source $f_{max} = \pi f_0$ and the cut-off frequency f_c (see equation (27) in appendix C), we obtain: $f_{max} = 4710 \text{ Hz} < f_c = 4959.592 \text{ Hz}$ which means that we can consider a Biot model without attenuation (the reader is referred to (Morency et al., 2009) for more details).

4 Qualitative analysis

4.1 Seismograms and spectrograms

In Figure 8-a, the experimental seismograms are shown. The directivity of the source is located in the vertical plane (yz) and along the longitudinal length y . The source injects essentially the energy in the vertical yz plane containing the line of receivers. The waves propagating in the perpendicular direction (plane xz) have smaller amplitudes than those propagating in the (yz) plane, and spend more time compared to the yz -plane waves to reach the vertical walls located far from the source axis and to come back to the receivers as observed by Jacob et al. (2008); Bergamo et al. (2014); Bodet et al. (2014). The amplitudes of these waves are thus strongly attenuated before reaching the receivers. The only main reflections that can be observed are coming from the bottom of the box. This is the reason why we apply PML absorbing layers in the 2 vertical planes (xz) parallel and far from the longitudinal line of receivers. This allows to reduce significantly the computational time in 3D configurations. However, it is important to study 3D different cases with 1) pure Dirichlet conditions (case 1) applied at all vertical walls and bottom of the box, 2) PMLs at all vertical walls except at the bottom (case 2) or 3) Full PMLs at all walls (case 3). This allows us to exhibit and identify the signals of interest and filter part of the signals reflected back from the walls,

to concentrate our efforts on the relevant signals and to evaluate if 2D simulations can reproduce the seismograms instead of using 3D simulations.

Figure 8 shows also the numerical seismograms for the different models (3D elastic, 2D elastic and 2D poro-elastic) in the Dirichlet case. We can clearly see the P-wave followed by a train of guided waves of the P-SV type. The P-wave, itself guided by the gradient of mechanical properties of the medium, corresponds to fast modes considered as essentially longitudinal. We can also see the reflections of the waves on the boundaries due to the considered Dirichlet conditions (case 1). However, in the PMLs and Full PMLs (cases 2 and 3 respectively) cases these reflections disappear (see Figures 9 and 10). In Figure 9 corresponding to case 2, the horizontal events are appearing in the 2D elastic and 2D poroelastic cases due to the reflection of the waves at the Dirichlet bottom boundary. However, no such horizontal events are appearing in the 3D elastic case because of the attenuation of the waves amplitudes due to 3D geometrical divergence attenuation. To avoid such reflections in the 2D elastic and poroelastic simulations and to be coherent with the non reflecting waves of the 3D case 2, we will apply Full PMLs (case 3) in the 2D simulations. In the spectrograms, in the case of Dirichlet conditions, the reflections contaminate the frequency signal (see Figure 11). Imposing absorbing conditions (C-PML) at the outer boundaries absorbs the reflections and makes the spectrogram clearer (see Figures 12 and 13). By comparing the PMLs and Full PMLs cases, one notices that the Dirichlet conditions imposed at the bottom of the medium in the PMLs case (case 2) create interferences represented by horizontal lines.

Therefore, in the next sections, we will thus continue our analyses by considering only the Full PMLs case in which no reflections are coming back into the computational domain.

4.2 Dispersion images

As in Park and Elrick (1998), a slant stack transform (an oblique summation of normalized signal amplitudes in the frequency domain) is applied to the experimental and simulated seismograms of Figure 10 and gives us the dispersion images shown in Figure 14. We identify three principal modes on the image of experimental dispersion over the source-relative frequency band $[0.1 - 3000Hz]$. The maxima (in black in Figures 14) correspond to four modes: two low velocity P-SV modes (propagation modes) at Low Frequency (LF) in the $0.25-1 kHz$ frequency band (mode 0 and 1), and two P-modes (one principal: mode 2) at higher frequencies and higher velocities in the $1.25-2.5 kHz$ frequency band.

The dispersion images of the numerical elastic models (2D and 3D) in Figure 14 show clearly only two modes (mode 0 and 1). The mode 2 appears more clearly for the poroelastic model.

5 Quantitative analysis

5.1 First arrivals

The first-arrival (P-mode) time of the numerical data is picked at each trace and compared to both the theoretical (calculated for the unconsolidated granular medium) and experimental travel times. These travel times are shown on the time versus offset curve in Figure 15. Computed arrival times are matching experimental and theoretical results within a 5% error range. Furthermore, the experimental first arrival times have been picked with an error range of 5% too. Besides, an initial triggering time of approximately 0.0045s is taken into account in our comparisons as can be observed on Figure 15 close to the source at zero-offset. Moreover, the V_p models obtained by inverting these arrival times have less than 5% - 10 % errors.

5.2 Dispersion curves

The V_s model (see equation (1-b)) is obtained by simulated annealing inversion of the fundamental mode curve extracted from the dispersion diagram of the vertical component of experimental recorded signals. The V_s model has an error range of 10-15% that corresponds to 5 % data misfit error and 15% error on α_s parameter (see Bodet et al. (2014) for more details on error estimations). For this V_s model, we compute the solutions with our UNISOLVER code and the related dispersion diagrams. The dispersion curves picked for the P-SV modes identified on the dispersion images (Figure 14) clearly fit experimental and theoretical dispersion (Figure 16). The P-SV theoretical dispersion curves are calculated using CPS/Computing Programs for Seismology (Herman et al 2013).

The P-mode picked on the 3D elastic and 2D elastic dispersion images appeared noisy due to its weak amplitude. But the P-mode picked in the 2D poro-elastic case is better represented compared to experimental data and theoretical dispersion. The theoretical dispersion is computed with the CPS code that uses the Thomson-Haskell matrix propagator technique and includes the complex-valued roots of the dispersion equation. Figure 16 shows the peaks of the energy maxima corresponding to the identified modes on the dispersion images (see Figure 14). This confirms that the modes identified on the numerical dispersion images correspond to the fundamental mode (mode 0) and to the second propagation mode (mode 1). The first P-mode (mode 2) is not visible enough on the dispersion image of the 3D/2D elastic model but it appears more clearly in the poro-elastic one.

We have been able to reproduce qualitatively the modes 0 and 1 but not the modes 2 related to P-modes. This is mainly due to the way the source is introduced numerically. Indeed, the way the source is modelled is crucial to detect all the main surface and P-SV modes (0, 1) as well as volumic wave modes (P modes 2 and higher), and to better reproduce numerically the waveforms of the experimental data. The next section is devoted to this aspect and tries to bring some answers about the source modelling.

6 Impact of the numerically modelled source

Source configuration

Instead of considering a source defined by a stick with vibratory displacement, we consider an equivalent virtual force point source at different depths with the same inclination as the stick and the same time signal source injected during the experiment. We have considered different depths, i.e., 3.76, 4.7, 5.64, 6.58, 7.52 *cm*, respectively. The corresponding lengths of the stick are 4, 5, 6, 7, 8 *cm*, respectively (see Figure 17). The best results are obtained in the case of a 8 *cm* deep source case modelled as a point source. We choose this case because better waveforms and better modes description have been obtained as discussed hereafter. For sake of simplicity, we are not showing the related dispersion images for the other virtual source depths.

Waveforms comparison

The numerical seismograms (2D elastic and 2D poro-elastic models) in the 8 *cm* deep source case are more similar to the seismograms of the experiment (see Figure 18) than the pure stick case (see Figure 10). In Figures 19-a,b, the seismograms are scaled with offset r for receivers reasonably far (5 *cm* away) from the source. Quantitatively, we can see in Figure 19-a that the first wave trains of the 2D elastic and 2D poro-elastic models (i.e, before ≈ 0.012 *s*) are very similar to the experimental ones. However, we notice that the computed Rayleigh waveforms have overestimated amplitudes when compared to experimental surface waveforms after ≈ 0.012 *s*. On the contrary, in the 8 *cm* deep source case (Figure 19-b), the first wave train is almost superimposed to the experimental data waveform before ≈ 0.012 *s*, and the order of magnitude of the amplitudes of surface waves is similar to the amplitudes of the experimental data, which is very encouraging. The numerical modeling matches better the solution when the location of the source is deeper because the medium is better illuminated from below, between the source and the receivers, which is well known for instance by geophysicists working at near surface scales in passive seismics with local earthquakes located close to the surface at a reasonable depth in the crust. Indeed, great part of the energy of the source is transmitted from below and through the shallow layers of the medium and then excite the high frequency (small wavelength) contents of the medium. More particularly, the 2D poroelastic waveforms are matching better the real data in amplitude and phase, and more specifically the first arrivals in time and amplitude of the real data than the pure elastic waves that are more delayed in time, which can be explained by faster poroelastic V_p velocities (V_{pfast}).

In the stick source case (Figure 19-a), the amplitudes of the Rayleigh waves are very similar for both poroelastic and elastic waves but they remain larger than the amplitudes of the surface waves present in the real data. For a 8 *cm* deep source (Figure 19-b), the amplitudes have decreased and are closer to those of the real data. However, the elastic waves are delayed in time with respect to the poroelastic waves in particular in the first wave train and have smaller amplitudes than poroelastic waves and real data. This can be due to faster poroelastic velocities.

As a future perspective, it would be thus important to model the source more properly in order to better reproduce the waveforms in terms of phase and amplitude. To obtain a better source, the source signal in time and space, its spatial spreading and its location at depth should be inverted. In the case of comparisons

between 3D real data and 2D simulated data, a 3D-to-2D transformation should be first applied to real data through time convolution corrections and rescaling corrections depending on the offset r . Then, for both 2D or 3D simulations, different clusters of receivers should be considered and the real data should be stacked over these clusters for signal coherency and deconvolved with the simulated data for the current model we are studying. Then, the spectral ratios of the experimental stacked data and simulated data can be used to obtain an equivalent/virtual source that explains better all the recorded waveforms in phase and amplitude. The details of building such source wavelet are well explained in Forbriger et al. (2014). The source wavelet could even be more suitably corrected by applying similar procedures as those proposed by the authors mentioned before in the data section 2.2 (Schäfer et al., 2012, 2014; Groos et al., 2013, 2014a; Forbriger et al., 2014) and more particularly when 3D-to-2D transformations are used.

Finally, using a multi-frequency inversion process, we could invert both the source and the recorded waveforms progressively from low to high frequencies and this way the (poro-)elastic model as well as the source wavelet will be improved. Such source and model inversions can be performed by using procedures similar to those also developed by Schäfer et al. (2013, 2014); Groos et al. (2013, 2014a); Forbriger et al. (2014) for near-surface applications and full waveform inversions using efficient 3D-to-2D transformations to the data.

Dispersion analysis

In Figure 20, we can see the very good similarity of the numerical dispersion images with the experimental one. In the previous section, the P-modes (mode 2) were not clearly reproduced in terms of amplitude. On the contrary, we obtain here the same patterns with very pronounced P-modes. These modes are very well represented in both elastic and poro-elastic cases. In the poro-elastic case, results are slightly improved. This can be clearly observed on the dispersion curves of Figure 21. All these results show the crucial importance of the data sensitivity to the source modelling and particularly to the source location at depth. The deeper is the source the more the P -modes can be recovered and moved towards lower frequencies. Since these P -modes are more pronounced, the $P - SV$ wave modes are less visible even if they are still existing but with less intensity. Of course, if the source location is too deep, surface waves will not be generated. This opens new perspectives to better define the source: inversion of its location at depth and a better spatial spreading description could be done.

7 Conclusions

In this study, the V_p - V_s model has been well integrated in elastic and poroelastic codes. The results obtained from qualitative and quantitative points of view are improved compared to those presented in (Bodet et al., 2014) in the case of zero overpressure, corresponding here to the dry (not fluidized) case. Numerical first arrivals and dispersion curves are very close to those of the experimental and theoretical ones.

The rheology considered (purely elastic or poroelastic) and the source location play an important role in the modelling of this kind of complex medium. Indeed, a poroelastic model combined with an acoustic source located at an adequate depth

gives better results than purely elastic models and sources (a force point source or a vibratory stick) placed close to or at the surface . The fundamental mode as well as the higher modes (such as the P-modes) are better defined and are more comparable to those of the real experimental data.

The model has been validated for dry media. In future works, we plan to study fluidized media with overpressure or media partially saturated with fluids like water, and to improve the models by also inverting the shape and the location of the source. A more complete study will be considered with a 3D poroelastic model and we will also take into account attenuation effects through different viscoelastic models. This will pave the way to study gas or fluid/water detection and also to monitor some areas for CO₂ storage, mitigation of flash floods, etc...

Acknowledgments

The authors thank the Université Fédérale de Toulouse Midi-Pyrénées (UFT-MIP) and Occitanie Region Research Council under DIMSCALE3D project, the CALMIP mesocentre in Toulouse, France, under supercomputing project *P1135–2021A* and *P1135–2022A*, and computing platform NUWA of the OMP/Observatoire Midi-Pyrénées, France. The authors thank the reviewers for their very useful suggestions and remarks to improve the manuscript.

Compliance with Ethical Standards

- Conflict of Interest: All authors declare that they have no conflict of interest.
- Ethical approval: This article does not contain any studies with human participants or animals performed by any of the authors.

References

- Bachrach R, Dvorkin J, Nur A (1998) High-resolution shallow-seismic experiments in sand, part ii: Velocities in shallow unconsolidated sand. *Geophysics* 63(4):1234–1240
- Bergamo P, Bodet L, Socco LV, Mourgues R, Tournat V (2014) Physical modelling of a surface-wave survey over a laterally varying granular medium with property contrasts and velocity gradients. *Geophys J Int* 197(1), DOI <http://dx.doi.org/10.1111/1.4712020>
- Biot MA (1956a) Theory of propagation of elastic waves in a fluid-saturated porous solid. I: Low-frequency range. *J Acoust Soc Am* 28:168–178
- Biot MA (1956b) Theory of propagation of elastic waves in a fluid-saturated porous solid. II: Higher-frequency range. *J Acoust Soc Am* 28:179–191
- Bitri A, Grandjean G, Baltassat J (2002) Caractérisation du proche sous-sol le long de tracés linéaires par profilage sasw. In: In Journées AGAP, LCPC, p 503–506
- Bodet L, Jacob X, Tournat V, Mourgues R, Gusev V (2010) Elasticity profile of an unconsolidated granular medium inferred from guided waves: Toward acoustic monitoring of analogue models. *Tectonophysics* 496:99–104
- Bodet L, Dhemaied A, Martin R, Mourgues R, Rejiba F, Tournat V (2014) Small-scale physical modeling of seismic-wave propagation using unconsolidated granular media. *Geophysics* 79(6):T323–T339
- Carcione JM (2007) *Wave fields in real media: Theory and numerical simulation of wave propagation in anisotropic, anelastic, porous and electromagnetic media*, 2nd edn. Elsevier Science, Amsterdam, The Netherlands
- Carcione JM (2014) *Wave Fields in Real Media: Wave Propagation in Anisotropic, Anelastic, Porous and Electromagnetic Media*. Elsevier
- Chau M, El Baz D, Guivarch R, Spiteri P (2007) MPI implementation of parallel subdomain methods for linear and nonlinear convection–diffusion problems. *Journal of Parallel and Distributed Computing* 67(5):581–591, DOI <https://doi.org/10.1016/j.jpdc.2007.01.003>, URL <https://www.sciencedirect.com/science/article/pii/S0743731507000056>
- Dumbser M, Käser M (2006) An arbitrary high-order discontinuous Galerkin method for elastic waves on unstructured meshes-II. The three-dimensional isotropic case. *Geophys J Int* 167(1):319–336, DOI 10.1111/j.1365-246X.2006.03120.x
- El Baz D, Miellou J, Spiteri P (2001) Asynchronous Schwarz alternating methods with flexible communication for the obstacle problem. *Calculateurs Parallèles, Réseaux et Systèmes Répartis* 13(01):47–66
- El Baz D, Frommer A, Spiteri P (2005) Asynchronous iterations with flexible communication: contracting operators. *Journal of Computational and Applied Mathematics* 176:91–103
- Forbriger T, Groos L, Schäfer M (2014) Line-source simulation for shallow-seismic data. Part 1: theoretical background. *Geophysical Journal International* 198(3):1387–1404, DOI 10.1093/gji/ggu199, URL <https://doi.org/10.1093/gji/ggu199>, <https://academic.oup.com/gji/article-pdf/198/3/1387/1571450/ggu199.pdf>
- Foti S (2000) Multistation method for geotechnical characterization using surface waves. PhD thesis, Politecnico di Torino, Italy

- Ganji V, Gucunski N, Maher A (1997) Detection of underground obstacles by sasw method - numerical aspects. *Journal of Geotechnical and Geoenvironmental Engineering* 123:212–219
- Gassmann F (1951) Elastic waves through a packing of spheres. *Geophysics* 16(4):673–685
- Graves RW (1996) Simulating seismic wave propagation in 3D elastic media using staggered-grid finite differences. *Bull Seismol Soc Am* 86(4):1091–1106
- Groos L, Schäfer M, Forbriger T, Bohlen T (2013) Comparison of 1d conventional and 2d full waveform inversion of recorded shallow seismic rayleigh waves DOI 10.3997/2214-4609.20131337
- Groos L, Schäfer M, Butzer S, Forbriger T, Bohlen T (2014a) Challenges for 2-d elastic full waveform inversion of shallow-seismic rayleigh waves DOI 10.3997/2214-4609.20140532
- Groos L, Schäfer M, Forbriger T, Bohlen T (2014b) The role of attenuation in 2d full-waveform inversion of shallow-seismic body and rayleigh waves. *GEOPHYSICS* 79(6):R247–R261, DOI 10.1190/geo2013-0462.1
- Improta L, Zollo A, Herrero A, Frattini R, Virieux J, Dell'Aversana P (2002) Seismic imaging of complex structures by non-linear traveltime inversion of dense wide-angle data : application to a thrust belt. *Geophys J Int* 151:264–278
- Jacob X, Aleshin V, Tournat V, Leclaire P, Lauriks W, Gusev V (2008) Acoustic probing of the jamming transition in an unconsolidated granular medium. *Physical Review Letters* 100(15):158003
- Komatitsch D (1997) Méthodes spectrales et éléments spectraux pour l'équation de l'élastodynamique 2D et 3D en milieu hétérogène (Spectral and spectral-element methods for the 2D and 3D elastodynamics equations in heterogeneous media). PhD thesis, Institut de Physique du Globe, Paris, France, 187 pages
- Komatitsch D, Martin R (2007) An unsplit convolutional Perfectly Matched Layer improved at grazing incidence for the seismic wave equation. *Geophysics* 72(5):SM155–SM167, DOI 10.1190/1.2757586
- Le Meur H (1994) Tomographie tridimensionnelle à partir des temps des premières arrivées des ondes p et s. application à la région de Patras (Grèce). PhD thesis, Université de Paris VII, Paris, France
- Makse HA, Gland N, Johnson DL, Schwartz LM (1999) Why effective medium theory fails in granular materials. *Physical Review Letters* 83(24):5070
- Martin R, Komatitsch D (2009) An unsplit convolutional perfectly matched layer technique improved at grazing incidence for the viscoelastic wave equation. *Geophys J Int* 179(1):333–344, DOI 10.1111/j.1365-246X.2009.04278.x
- Martin R, Komatitsch D, Blitz C, Le Goff N (2008a) Simulation of seismic wave propagation in an asteroid based upon an unstructured MPI spectral-element method: blocking and non-blocking communication strategies. *Lecture Notes in Computer Science* 5336:350–363
- Martin R, Komatitsch D, Ezziani A (2008b) An unsplit convolutional perfectly matched layer improved at grazing incidence for seismic wave equation in poroelastic media. *Geophysics* 73(4):T51–T61, DOI 10.1190/1.2939484
- Martin R, Komatitsch D, Gedney SD, Bruthiaux E (2010) A high-order time and space formulation of the unsplit perfectly matched layer for the seismic wave equation using Auxiliary Differential Equations (ADE-PML). *Comput Model Eng Sci* 56(1):17–42

- Miellou J, El Baz D, Spiteri P (1998) A new class of asynchronous iterative methods with order intervals. *Math Comput* 67(01):237–255, DOI 10.1090/S0025-5718-98-00885-0
- Moczó P, Bystrický E, Kristek J, Carcione JM, Bouchon M (1997) Hybrid modeling of *P-SV* seismic motion at inhomogeneous viscoelastic topographic structures. *Bull Seismol Soc Am* 87:1305–1323
- Moczó P, Kristek J, Bystrický E (2001) Efficiency and optimization of the 3-D finite-difference modeling of seismic ground motion. *J Comput Acoust* 9(2):593–609
- Moczó P, Kristek J, Galis M, Pazak P (2010) On accuracy of the finite-difference and finite-element schemes with respect to p-wave to s-wave speed ratio. *Geophysical Journal International* 182(1):493–510
- Morency C, Tromp J (2008) Spectral-element simulations of wave propagation in porous media. *Geophys J Int* 175:301–345, DOI 10.1111/j.1365-246X.2008.03907.x
- Morency C, Luo Y, Tromp J (2009) Finite-frequency kernels for wave propagation in porous media based upon adjoint methods. *Geophys J Int* 179:1148–1168, DOI 10.1111/j.1365-246X.2009.04332
- Nazarian S, Stokoe K (1984) In situ shear wave velocities from spectral analysis of surface waves. In: *Proc. 8th Conf. on Earthquake Eng., Nice, France, vol 3*, pp 31–38
- Palermo A, Krödel S, Matlack KH, Zaccherini R, Dertimanis VK, Chatzi EN, Marzani A, Daraio C (2018) Hybridization of guided surface acoustic modes in unconsolidated granular media by a resonant metasurface. *Phys Rev Applied* 9:054026, DOI 10.1103/PhysRevApplied.9.054026
- Park S, Elrick S (1998) Predictions of shear-wave velocities in southern California using surface geology. *Bulletin of the Seismological Society of America* 88(3):677–685
- Pasquet S, Bodet L (2017) Swip: An integrated workflow for surface-wave dispersion inversion and profiling. *Geophysics* 82(6):WB47–WB61
- Pride SR, Berryman JG, Harris JM (2004) Seismic attenuation due to wave-induced flow. *J Geophys Res* 109:681–693
- Pu X, Palermo A, Cheng Z, Shi Z, Marzani A (2020) Seismic metasurfaces on porous layered media: Surface resonators and fluid-solid interaction effects on the propagation of rayleigh waves. *International Journal of Engineering Science* 154:103347, DOI <https://doi.org/10.1016/j.ijengsci.2020.103347>
- Ravaut C (2003) Tomographie sismique haute résolution de la croûte terrestre : inversion combiné des temps de trajet et des formes d’ondes de données sismiques réflexion/réfraction grand angle multitraces. PhD thesis, Université de Nice Sophia Antipolis, Nice, France
- Schön JH (2015) *Physical properties of rocks: Fundamentals and principles of petrophysics*. Elsevier
- Schäfer M, Groos L, Forbriger T, Bohlen T (2012) On the effects of geometrical spreading corrections for a 2d full waveform inversion of recorded shallow seismic surface waves. DOI 10.3997/2214-4609.20148327
- Schäfer M, Groos L, Forbriger T, Bohlen T (2013) 2d full waveform inversion of recorded shallow seismic rayleigh waves on a significantly 2d structure. *Near Surface Geoscience* 2013 DOI 10.3997/2214-4609.20131338

-
- Schäfer M, Groos L, Forbriger T, Bohlen T (2014) Line-source simulation for shallow-seismic data. part 2: Full-waveform inversion-a synthetic 2-d case study. *Geophysical Journal International* 198:1405–1418, DOI 10.1093/gji/ggu171
- Sidler R, Carcione JM, Holliger K (2014) A pseudospectral method for the simulation of 3-D ultrasonic and seismic waves in heterogeneous poroelastic borehole environments. *Geophysical Journal International* 196(2):1134–1151
- Tournat V, Gusev V (2010) Acoustics of unconsolidated “model” granular media: An overview of recent results and several open problems. *Acta Acustica united with Acustica* 96(2):208–224
- Xia J (2014) Estimation of near-surface shear-wave velocities and quality factors using multichannel analysis of surface-wave methods. *Journal of applied geophysics* 103:140–151
- Xia J, Miller R, Park C (1999) Estimation of near-surface shear-wave velocity by inversion of rayleigh waves. *Geophysics* 64(3):691–700
- Zaccherini R, Palermo A, Marzani A, Colombi A, Dertimanis V, Chatzi E (2020) Mitigation of rayleigh-like waves in granular media via multi-layer resonant metabarriers. *Applied Physics Letters* 117(25):254103, DOI 10.1063/5.0031113
- Zelt C, Smith R (1992) Seismic travelttime inversion for 2d crustal velocity structure. *Geophys J Int* 108:16–34
- Zeng YQ, Liu QH (2001) A staggered-grid finite-difference method with perfectly matched layers for poroelastic wave equations. *J Acoust Soc Am* 109(6):2571–2580, DOI 10.1121/1.1369783
- Zimmer MA, Prasad M, Mavko G, Nur A (2007) Seismic velocities of unconsolidated sands: Part 1—pressure trends from 0.1 to 20 mpa. *Geophysics* 72(1):E1–E13

A 3D elastic wave equations

The elastodynamics equations can be formulated at the second order in displacement as:

$$\begin{aligned}\rho \frac{\partial^2 u_i}{\partial t^2} &= \partial_j \sigma_{ij} + s_i, \\ \epsilon_{ij} &= \frac{1}{2} (u_{i,j} + u_{j,i}), \\ \sigma_{ij} &= \lambda \delta_{ij} \epsilon_{kk} + 2\mu \epsilon_{ij}.\end{aligned}$$

However, the first-order formulation (velocity-stress) of the 3D elastic wave equations for a linear, isotropic medium submitted to external forces are given by (Graves (1996)):

$$\begin{aligned}\rho \frac{\partial v_x}{\partial t} &= \frac{\partial \sigma_{xx}}{\partial x} + \frac{\partial \sigma_{xy}}{\partial y} + \frac{\partial \sigma_{xz}}{\partial z} + s_x, \\ \rho \frac{\partial v_y}{\partial t} &= \frac{\partial \sigma_{xy}}{\partial x} + \frac{\partial \sigma_{yy}}{\partial y} + \frac{\partial \sigma_{yz}}{\partial z} + s_y, \\ \rho \frac{\partial v_z}{\partial t} &= \frac{\partial \sigma_{xz}}{\partial x} + \frac{\partial \sigma_{yz}}{\partial y} + \frac{\partial \sigma_{zz}}{\partial z} + s_z, \\ \frac{\partial \sigma_{xx}}{\partial t} &= (\lambda + 2\mu) \frac{\partial v_x}{\partial x} + \lambda \left(\frac{\partial v_y}{\partial y} + \frac{\partial v_z}{\partial z} \right), \\ \frac{\partial \sigma_{yy}}{\partial t} &= (\lambda + 2\mu) \frac{\partial v_y}{\partial y} + \lambda \left(\frac{\partial v_x}{\partial x} + \frac{\partial v_z}{\partial z} \right), \\ \frac{\partial \sigma_{zz}}{\partial t} &= (\lambda + 2\mu) \frac{\partial v_z}{\partial z} + \lambda \left(\frac{\partial v_x}{\partial x} + \frac{\partial v_y}{\partial y} \right), \\ \frac{\partial \sigma_{xy}}{\partial t} &= \mu \left(\frac{\partial v_y}{\partial x} + \frac{\partial v_x}{\partial y} \right), \\ \frac{\partial \sigma_{xz}}{\partial t} &= \mu \left(\frac{\partial v_z}{\partial x} + \frac{\partial v_x}{\partial z} \right), \\ \frac{\partial \sigma_{yz}}{\partial t} &= \mu \left(\frac{\partial v_z}{\partial y} + \frac{\partial v_y}{\partial z} \right).\end{aligned}\tag{2}$$

In these equations, v_x , v_y , v_z are the velocity components; σ_{xx} , σ_{yy} , σ_{zz} , σ_{xy} , σ_{xz} , σ_{yz} are the stress components; s_x , s_y , s_z are the body-force components; ρ is the density; λ and μ are Lamé parameters.

B 2D elastic wave equations

In the 2D particular case, 2D elastic wave equations for an isotropic medium submitted to external forces can be written using a velocity-stress formulation such as the following linear and hyperbolic system (Dumbser and Käser (2006)):

$$\begin{aligned}
\rho \frac{\partial v_x}{\partial t} &= \frac{\partial \sigma_{xx}}{\partial x} + \frac{\partial \sigma_{xz}}{\partial z} + s_x, \\
\rho \frac{\partial v_z}{\partial t} &= \frac{\partial \sigma_{xz}}{\partial x} + \frac{\partial \sigma_{zz}}{\partial z} + s_z, \\
\frac{\partial \sigma_{xx}}{\partial t} &= (\lambda + 2\mu) \frac{\partial v_x}{\partial x} + \lambda \frac{\partial v_z}{\partial z}, \\
\frac{\partial \sigma_{zz}}{\partial t} &= (\lambda + 2\mu) \frac{\partial v_z}{\partial z} + \lambda \frac{\partial v_x}{\partial x}, \\
\frac{\partial \sigma_{xz}}{\partial t} &= \mu \left(\frac{\partial v_z}{\partial x} + \frac{\partial v_x}{\partial z} \right),
\end{aligned} \tag{3}$$

where λ and μ are Lamé parameters, ρ is the density, and s_x and s_z are the space dependent source terms in x and z directions. The compressional stress components are given by σ_{xx} and σ_{zz} , and the shear stress is σ_{xz} . The components of particle velocities in direction x and z are denoted by v_x and v_z , respectively.

C 2D poro-elastic wave equations

Porous materials are made of a solid phase (called the frame) and of a fluid phase, and can be considered as an interconnected network of pores inside the solid (Pride et al., 2004). When a fluid flow is able to cause the solid to deform, the material is called poroelastic. Unconsolidated granular media can be seen as a poroelastic material in which air or water can play the role of the fluid and grains the solid. Poroelastic materials are most of the time modeled using the Biot theory (Biot (1956a) and Biot (1956b)). The differential or "strong" formulation of the poroelastic wave equations can be written as (Carcione, 2007), (Carcione, 2014):

$$\rho \partial_t^2 u^s + \rho_f \partial_t^2 w = \nabla \cdot (C : \nabla u^s - \alpha P^f I), \tag{4}$$

$$\rho_f \partial_t^2 u^s + \rho_w \partial_t^2 w = -\nabla P^f - K \partial_t w, \tag{5}$$

$$P^f = -\alpha M \nabla \cdot u^s - M \nabla \cdot w, \tag{6}$$

where $u^s = (u_i^s)_{i=1,2}$, $w = \Phi (u^f - u^s)$ and $u^f = (u_i^f)_{i=1,2}$ are respectively the solid, relative, and fluid displacement vectors; Φ is the porosity and C is the stiffness tensor of the isotropic elastic solid matrix, defined as:

$$\sigma_{ij}^s = (C : \epsilon)_{ij} = \lambda_s \delta_{ij} \epsilon_{kk} + 2\mu \epsilon_{ij}, \tag{7}$$

$$\epsilon_{ij} = \frac{1}{2} \left(\frac{\partial u_i^s}{\partial x_j} + \frac{\partial u_j^s}{\partial x_i} \right), \tag{8}$$

$$P^f = -\alpha M \nabla \cdot u^s - M \nabla \cdot w, \tag{9}$$

where indices i and j can be here 1 or 2 in 2D and with the Einstein convention of implicit summation over a repeated index. P^f is the pressure in the fluid. σ^s and ϵ are respectively the stress and strain tensors of the isotropic elastic solid frame. The stress tensor of the fluid-filled solid matrix is $\sigma = \sigma^s - \alpha P^f I$, and $\rho = \Phi \rho_f + (1 - \Phi) \rho_s$ is the density of the saturated medium, where ρ_s and ρ_f are the solid and fluid densities, respectively. The apparent density is $\rho_w = \alpha \frac{\rho_f}{\Phi}$

where a denotes the tortuosity. The shear modulus is μ and $\lambda_s = \lambda - \alpha^2 M$ is the Lamé coefficient in the solid matrix, where λ is the Lamé coefficient of the saturated matrix. The α and M variables are functions of the porosity and bulk moduli of the fluid and solid components of the porous medium and are given by the following expressions:

$$\alpha = 1 - \frac{K_{fr}}{K_s}, \quad (10)$$

$$M = 1/[\Phi/K_f + (\Phi - \alpha)/K_s], \quad (11)$$

where K_{fr} is the incompressibility modulus of the porous frame, K_s is the incompressibility modulus of the solid matrix, and K_f is the incompressibility modulus of the fluid. The viscous damping coefficient is:

$$K = \kappa/\eta, \quad (12)$$

where κ is the permeability of the solid matrix and η is the fluid viscosity. Equations (4) to (7) can be written using a first order velocity-stress formulation:

$$\left(\rho_w \rho - \rho_f^2\right) \partial_t v^s = \rho_w \nabla \cdot \sigma + \rho_f \nabla P^f + \rho K v^f, \quad (13)$$

$$\left(\rho_w \rho - \rho_f^2\right) \partial_t v^f = -\rho_f \nabla \cdot \sigma - \rho \nabla P^f - \rho_f K v^f, \quad (14)$$

$$\partial_t \sigma = C : \nabla v^s - \alpha \partial_t P^f I, \quad (15)$$

$$\partial_t P^f = -\alpha M \nabla \cdot v^s - M \nabla \cdot v^f, \quad (16)$$

where $v^s = (v_i^s)_{i=1,2}$ and $v^f = \partial_t w = (v_i^f)_{i=1,2}$ are the solid and filtration velocity vectors, respectively. σ is the effective stress tensor of the porous medium. As in [Zeng and Liu \(2001\)](#), using the trace of the strain tensor $Tr(\epsilon) = \epsilon_{ii}$ and an auxiliary variable ξ , we rewrite the system as:

$$\left(\rho_w \rho - \rho_f^2\right) \partial_t v_i^s = \rho_w \partial_j \sigma_{ij} + \rho_f \partial_i P^f + \rho K v_i^f, \quad (17)$$

$$\left(\rho_w \rho - \rho_f^2\right) \partial_t v_i^f = -\rho_f \partial_j \sigma_{ij} - \rho \partial_i P^f - \rho_f K v_i^f, \quad (18)$$

$$\epsilon_{ij} = \frac{1}{2} (\partial_j v_i^s + \partial_i v_j^s), \quad (19)$$

$$\partial_t \xi = -\partial_i v_i^f, \quad (20)$$

$$P^f = -\alpha M Tr(\epsilon) + M \xi, \quad (21)$$

$$\sigma_{ij}^s = \lambda^s \delta_{ij} Tr(\epsilon) + 2\mu \epsilon_{ij}, \quad (22)$$

$$\sigma_{ij} = \sigma_{ij}^s - \alpha P^f \delta_{ij}. \quad (23)$$

This system of equations has seven wave eigenvalues related to seven wave velocity modes (instead of five for the elastic case). Those wave velocities are $\pm V_{pFAST}$, $\pm V_{pSLOW}$, $\pm V_s$ and 0. The shear velocity V_s and the fast and slow P-wave velocities (V_{pFAST} and V_{pSLOW}) can be expressed as ([Sidler et al., 2014](#)):

$$V_s = \sqrt{\frac{\mu}{a_1}}, \quad (24)$$

Parameters of the poroelastic model	
Φ	Porosity
ρ	Density of the saturated medium
ρ_s	Density of the solid
ρ_f	Density of the fluid
ρ_w	Apparent density
K_s	Incompressibility modulus of the solid matrix
K_f	Incompressibility modulus of the fluid
K_{fr}	Incompressibility modulus of the porous frame
κ	Permeability of the solid matrix
η	Fluid viscosity
a	Tortuosity
λ	Lamé coefficient of the saturated matrix
λ_s	Lamé coefficient in the solid matrix
μ	Shear modulus

Table 1. Parameters of the poroelastic model.

$$V_{pFAST} = \sqrt{\frac{-b_1 + \sqrt{\Delta}}{2a_1}}, \quad (25)$$

$$V_{pSLOW} = \sqrt{\frac{-b_1 - \sqrt{\Delta}}{2a_1}}, \quad (26)$$

where

$$\begin{aligned} a_1 &= \rho_{11}\rho_{22} - \rho_{12}^2, \\ b_1 &= -S\rho_{22} - R\rho_{11} + 2ga\rho_{11}, \\ c_1 &= SR - ga^2, \\ \rho_{11} &= \rho + \rho_f\Phi(a - 2), \\ \rho_{12} &= \Phi\rho_f(1 - a), \\ \rho_{22} &= a\rho_f\Phi, \\ S &= \lambda + 2\mu, \\ R &= M\Phi^2, \\ \Delta &= b_1^2 - 4a_1c_1, \\ ga &= M\Phi(\alpha - \Phi). \end{aligned}$$

In Table 1, a summary of the different parameters of the poroelastic model is provided.

Biot's characteristic frequency f_c defines the transition between two poroelastic regimes (with or without attenuation) and is given as follows (see (Biot, 1956b), (Carcione, 2007) and (Morency and Tromp, 2008)):

$$f_c = \min\left(\frac{\eta\Phi}{2\pi a\rho_f\kappa}\right), \quad (27)$$

see parameters in Table 1.

In our study, the maximum frequency range f_{max} of the source is such that $f_{max} < f_c$. Therefore, in the experimental and numerical modeling of unconsolidated granular media under study, we choose to stay in the poroelastic regime without attenuation.

D Performances of UNISOLVER parallel code

The 4-th order 3D UNISOLVER parallel code has been scaled over different numbers of processors (up to 400) of Olympe supercomputer at CALMIP computing centre of Toulouse (France) by using MPI (Message-Passing-Interface) library. The computational domain has been cut along the longitudinal y-axis (from 20 points down to 5 grid points per processor along the y-axis). A buffer overlapping corresponding to two grid points between subdomains (one subdomain per processor) is used to communicate the particle velocities and stresses and material properties between processors via 'MPI_Send' and 'MPI_Recv' communication operations. As we can see in Figure 22, the strong scaling obtained by measuring the CPU time versus the number of processors is very satisfactory, despite the use of blocking communication operations. This strategy is classical (see (Komatitsch and Martin, 2007)).

We underline that asynchronous iterative schemes of computation which cover communications by computations in the inner subdomains as depicted in (Miellou et al., 1998; El Baz et al., 2001; Chau et al., 2007; El Baz et al., 2005; Martin et al., 2008a) are also very efficient.




Fig. 4. Experimental traces representing the normal component of particle velocity (V_z) not filtered and filtered as well as their difference (noise) at receivers 10 (a), 15 (b) and 20 (c), respectively.




Fig. 5. The 3D numerical model is discretised by elements of $5 \times 10^{-4} \text{ m}$ in each direction of space for a mesh of $70 \times 2000 \times 430$ points ($0.35 \text{ m} \times 1 \text{ m} \times 0.215 \text{ m}$). Dirichlet conditions (case 1) or absorbing PML layers composed of 15 points each (cases 2 and 3, i.e PMLs or Full PMLs) are applied on the outer boundaries except at the free surface. The free surface is defined at the top of the computational domain. The force source (in red) is implemented with an angle of 20° from the normal to the free surface, to meet the experimental configuration (see the 2D numerical setup in Figure 6). The receivers (dashed line in green) are spaced every $5 \times 10^{-3} \text{ m}$ (10 grid points) at the free surface.




Fig. 6. The 2D numerical model is discretised by elements of $5.10^{-4}m \times 5.10^{-4}m$ for a mesh of 2000×430 points ($1m \times 0.215m$). Absorbing PML layers composed of 15 points each one or Dirichlet conditions are applied to the outer boundaries except the free surface which is defined at the top of the computational domain. The force source (in red) is implemented with an angle of 20° from the normal to the free surface and injected at every source point along the stick length, to meet the experimental configuration and the stick form. The receivers (dashed line in green) are spaced every $5 \times 10^{-3}m$ (10 grid points) at the free surface.




Fig. 7. The different velocities computed for the elastic (V_s and V_p) and poroelastic ($V_{s\text{eff}}$, $V_{p\text{FAST}}$ and $V_{p\text{SLOW}}$) models. The difference between the poroelastic and elastic shear velocities is very small and is thus multiplied by 10^3 to see it more clearly.




Fig. 8. Comparison between experimental filtered (a), 3D elastic (b), 2D elastic (c) and 2D poroelastic (d) seismograms (vertical component of particle velocity) in the Dirichlet case.




Fig. 9. Comparison between experimental filtered (a), 3D elastic (b), 2D elastic (c) and 2D poroelastic (d) seismicograms (vertical component of particle velocity) in the PMLs case.




Fig. 10. Comparison between experimental filtered (a), 3D elastic (b), 2D elastic (c) and 2D poroelastic (d) seismicograms (vertical component of particle velocity) in the Full PMLs case.




Fig. 11. Comparison between experimental (a), 3D elastic (b), 2D elastic (c) and 2D poroelastic (d) spectrograms in the Dirichlet case.




Fig. 12. Comparison between experimental (a), 3D elastic (b), 2D elastic (c) and 2D poroelastic (d) spectrograms in the PMLs case.




Fig. 13. Comparison between experimental (a), 3D elastic (b), 2D elastic (c) and 2D poroelastic (d) spectrograms in the Full PMLs case.




Fig. 14. Comparison between experimental filtered (a), 3D elastic (b), 2D elastic (c) and 2D poroelastic (d) dispersion images in the Full PMLs case with stick source at the surface.




Fig. 15. First arrival times of the 3D elastic, 2D elastic and 2D poroelastic models compared to the experimental and analytical first arrival times.




Fig. 16. Dispersion curves of 3D elastic (a), 2D elastic (b) and 2D poro-elastic (c) seismograms compared to experimental and analytical dispersion curves with stick source at the surface.




Fig. 17. Numerical setup for the 8 cm deep source case for the 2D elastic and 2D poroelastic model cases.




Fig. 18. Experimental filtered seismogram (a) compared to the 2D elastic (b) and 2D poro-elastic (c) seismograms in the 8 *cm* deep source case.




Fig. 19. (a) Comparison of the numerical seismograms (for the 2D elastic and 2D poro-elastic models) with the experimental filtered ones at receivers 10, 15, and 20 in the pure (original) stick case (time in seconds). (b) Same thing but in the 8 cm deep source case. All the seismograms are zoomed over the first 30 ms because there is no signal after 25 ms in the numerical seismograms due to the PML absorbing conditions.




Fig. 20. Experimental dispersion image (a) compared to the 2D elastic (b) and 2D poro-elastic (c) dispersion images in the 8 *cm* deep source case.




Fig. 21. Dispersion curves for the 2D elastic (a) and 2D poro-elastic (b) models in the 8 *cm* deep source case compared to experimental and analytical dispersion curves.




Fig. 22. Strong scaling of the UNISOLVER code over 200 up to 400 processors on Olympe supercomputer. Ideal and numerical tests scaling curves are shown.