

Planar alignment of liquid crystal molecules along self-assembled GaAs quantum dashes

Hugo Villanti, Jean-Baptiste Doucet, Sébastien Plissard, Alexandre Arnoult, Benjamin Reig, Laurent Dupont, Véronique Bardinal

▶ To cite this version:

Hugo Villanti, Jean-Baptiste Doucet, Sébastien Plissard, Alexandre Arnoult, Benjamin Reig, et al.. Planar alignment of liquid crystal molecules along self-assembled GaAs quantum dashes. 50th International Micro and Nano Engineering Conference MNE2024, Sep 2024, Montpellier, France. hal-04939064

HAL Id: hal-04939064 https://laas.hal.science/hal-04939064v1

Submitted on 10 Feb 2025 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Planar alignment of liquid crystal molecules along self-assembled GaAs quantum dashes

Hugo Villanti ^a, <u>Jean-Baptiste Doucet</u> ^a, Sébastien Plissard ^a, Alexandre Arnoult ^a, Benjamin Reig ^a, Laurent Dupont ^b and Véronique Bardinal ^a

^a LAAS-CNRS, Université de Toulouse, CNRS, 7 Avenue du Colonel Roche, 31400 Toulouse, France ^b Optics department, IMT Atlantique Technopôle Brest-Iroise CS 83818 29238 Brest cedex 03 France

e-mail: <u>bardinal@laas.fr</u>

Dynamically-reconfigurable photonic devices such as spectrally-tunable VCSELs sources (verticalcavity surface-emitting lasers) or spectrally-tunable photodiodes are of major interest for many applications in optical instrumentation, such as compact gas sensing or biomedical imaging. The most mature way for producing a tunable VCSEL is based on the insertion of a MEMS (moving electromechanical system) inside or above the III-V semiconductor active device. However, this approach presents several limitations due to mechanical vibrations. Exploiting instead birefringence effects in a liquid crystal (LC) intracavity layer is a promising solution, as it would enable better wavelength control and stability.

However, LC-based tunable laser diode technology is still in its infancy due to the complexity of aligning liquid crystal molecules inside a III-V semiconductor optoelectronic device. To address this issue, the authors previously developed a polymer-based LC microcell (μ -cell) technology including a sub-wavelength period grating nano-imprinted in a SU-8 resist for LC alignment [1] (figure 1). A high finesse tunable optical filter, as well as a tunable photodiode [2] and an optically-pumped tunable VCSEL [3] could be demonstrated using this hybrid method. To further improve tuning performances and reduce the complexity of the technology, we demonstrate in this work that liquid crystal molecules can be directly aligned by GaAs anisotropic self-assembled nanocrystals, suppressing thus the need for inserting and patterning an organic alignment layer. The optimized conditions for the epitaxial growth and *in situ* annealing of self-assembled GaAs quantum dashes (QDHs) suitable for LC alignment (figure 2) are presented, as well as the process developed for the fabrication of a hybrid LC- μ cell including such elongated nanostructures. We show that LC alignment based on QDHs is as efficient as that obtained along the grooves of the SU-8 nanograting and what is more, with lower electrical consumption.

- [1] Sadani, B., Boisnard, B., Lafosse, X., Camps, T., Doucet, J. B., Daran, E., ... & Bardinal, V. (2018). Liquidcrystal alignment by a nanoimprinted grating for wafer-scale fabrication of tunable devices. IEEE Photonics Technology Letters, 30(15), 1388-1391.
- [2] Levallois, C., Sadani, B., Boisnard, B., Camps, T., Paranthoen, C., Pes, S., ... & Bardinal, V. (2018). Liquid crystal-based tunable photodetector operating in the telecom C-band. Optics Express, 26(20), 25952-25961.
- [3] B. Boisnard, C. Levallois, C. Paranthoen, S. Pes, T. Camps, B. Sadani, K. Tavernier, S. Bouchoule, L. Dupont, M. Alouini, P. Debernardi, and V. Bardinal, CW operation of a tunable 1550 nm VCSEL integrating liquid-crystal microcells, IEEE Photonics Technology Letters, vol. 32, no. 7, pp. 391 394, 2020 4.
- [4] C. Paranthoen et al., 33 nm wavelength tuning of a 1550 nm VCSEL in CW operation based on the liquid crystal micro-cells technology, 2021 27th International Semiconductor Laser Conference (ISLC), Potsdam, Germany, 2021, pp. 1-2, doi: 0.1109/ISLC51662.2021.9615666.



Figure 1. AFM image of the nanograting (height: 48 nm/period 200 nm) used as a reference. This grating is fabricated by soft nano-imprint in a SU-8 resist layer and already proven for planar alignment of nematic liquid crystal molecules in a microcell (image area: 0.5 x 1 µm²).



Figure 2. AFM image of the self-assembled anisotropic GaAs quantum dashes (QDHs) (average height: 21 nm, density: ~8 QDHs/μm²) fabricated by droplet epitaxy to demonstrate the feasibility of direct alignment of LC molecules in a microcell on a GaAs substrate: (image area: 1x1 μm²).